Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	X NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OF
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
NOTICE OF INTENTION TO DEEPEN WELL	NOTICE OF INTENTION TO PLUG WELL
Monument, New	Mexico August 10, 1936
OIL CONSERVATION COMMISSION,	Place Date
Santa Fe, New Mexico.	
Gentlemen:	
Following is a notice of intentiton to do certain work as	s decaribed between
Amerada Petroleum Corporation State	TTT or
Company or Operator Lease	Well No. 2 in NW2 NW4
, rt	_, N. M. P. M., Monument
Lea County.	Field
Casing and fittings will be	
Casing and fittings will be tested indisturbed for thirty minutes. If no does drilled out of the assistant the desired of the desired out of the d	a
Casing and fittings will be tested indisturbed for thirty minutes. If no does drilled out of the assistant the desired the des	casing was set in this well at 2490° and cems. d with 1200% pump pressure and allowed to strop in pressure results the cement will then set test of 1200% pressure again applied to the contract minutes. If no drop in pressure results the center of the contract minutes.
Casing and fittings will be tested indisturbed for thirty minutes. If no doe drilled out of the casing and the same well and allowed to stand undisturbed for the drilling will then be resumed.	casing was set in this well at 2490' and cems. d with 1200% pump pressure and allowed to sirop in pressure results the cement will them se test of 1200% pressure again applied to the continuous and allowed to sirop in pressure results and allowed to the continuous and allowed to sirop in pressure results and allowed to sirop in pressure results.
Casing and fittings will be tested and sturbed for thirty minutes. If no doe drilled out of the casing and the same well and allowed to stand undisturbed for the drilling will then be resumed.	casing was set in this well at 2490' and cems. d with 1200% pump pressure and allowed to sirop in pressure results the cement will then se test of 1200% pressure again applied to the thirty minutes. If no drop in pressure results the cement will then by thirty minutes. If no drop in pressure results the cement will then be the component of the component of the component of the cement will then be the cement will be the c
Casing and fittings will be tested and sturbed for thirty minutes. If no doe drilled out of the casing and the same sell and allowed to stand undisturbed for the drilling will then be resumed.	casing was set in this well at 2490' and cems. d with 1200% pump pressure and allowed to sirop in pressure results the cement will them se test of 1200% pressure again applied to the continuous and allowed to sirop in pressure results and allowed to the continuous and allowed to sirop in pressure results and allowed to sirop in pressure results.
Casing and fittings will be tested and sturbed for thirty minutes. If no deed rilled out of the casing and the same all and allowed to stand undisturbed for the drilling will then be resumed.	casing was set in this well at 2490' and cems. d with 1200% pump pressure and allowed to strop in pressure results the cement will then see test of 1200% pressure again applied to the pressure and allowed to the test of 1200% pressure again applied to the pressure results and the pressure results again applied to the pressure again applied to the pressure again applied to the pressure results again applied to the pressure again appli
Casing and fittings will be tested and sturbed for thirty minutes. If no deed rilled out of the casing and the same all and allowed to stand undisturbed for the drilling will then be resumed.	casing was set in this well at 2490' and cems. If with 1200% pump pressure and allowed to strop in pressure results the cement will then see test of 1200% pressure again applied to the thirty minutes. If no drop in pressure results the cement will then be test of 1200% pressure again applied to the thirty minutes. If no drop in pressure results the cement will then be test of 1200% pressure again applied to the company of thirty minutes. If no drop in pressure results the cement will then be test of 1200% pressure again applied to the company of the comp
Casing and fittings will be tested and sturbed for thirty minutes. If no does drilled out of the casing and the same sell and allowed to stand undisturbed for the drilling will then be resumed. Oroved————————————————————————————————————	casing was set in this well at 2490' and cems. I with 1200% pump pressure and allowed to sirop in pressure results the cement will them he test of 1200% pressure again applied to the pressure again applied to the pressure results in a drop in pressure results the cement will them he test of 1200% pressure again applied to the pressure results in a drop in pressure results again applied to the pressure again applied to the
Casing and fittings will be tested and sturbed for thirty minutes. If no doe drilled out of the casing and the same well and allowed to stand undisturbed for the drilling will then be resumed.	casing was set in this well at 2490' and cems. If with 1200% pump pressure and allowed to strop in pressure results the cement will then see test of 1200% pressure again applied to the thirty minutes. If no drop in pressure results the cement will then be test of 1200% pressure again applied to the thirty minutes. If no drop in pressure results the cement will then be test of 1200% pressure again applied to the company of thirty minutes. If no drop in pressure results the cement will then be test of 1200% pressure again applied to the company of the comp