

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

JUN 30 11 19 AM '67

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name W.L. Cortez
9. Well No. 1
10. Field and Pool, or Wildcat Lumont - Queen
12. County La

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/>
2. Name of Operator Admiral Drilling Company
3. Address of Operator P. O. Box 148, Roswell, New Mexico
4. Location of Well UNIT LETTER <u>I</u> , <u>3300</u> FEET FROM THE <u>GROUND</u> LINE AND <u>100</u> FEET FROM THE <u>East</u> LINE, SECTION <u>22</u> TOWNSHIP <u>34-N</u> RANGE <u>51-E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3574'

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well was plugged & abandoned in the following manner: Set 25 sk common cement plug across perforations 3430-3506. Cut off 2-7/8" casing - 3303'. Spotted 25 sk common cement plug from 3127-3387. removed BOP & tubinghead & cut off casinghead. Set 10 sk common cement plug from 10-70' in top of 5-1/2" casing. Set 3 sk cement plug in 5-1/2" x 8-5/8" casing annulus. 14 mud was left between all cement plugs. 8-5/8" & 5-1/2" casing strings remain intact. Installed dry hole marker. Well P & A 6/21/67

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed  
SIGNED O. D. Bretches TITLE District Drilling Supervisor DATE 6/29/67

APPROVED BY John W. Runyan TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY: