

DISTRICT I

P.O. Box 1980, Hobbs, NM 88241

DISTRICT II

P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

| | |
|--|--|
| WELL API NO. | 30-025-05794 |
| 5. Indicate Type of Lease | STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> |
| 6. State Oil / Gas Lease No. | |
| 7. Lease Name or Unit Agreement Name | North Monument G/SA Unit Blk. 16 |
| 8. Well No. | 14 |
| 9. Pool Name or Wildcat | Eunice Monument G/SA |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) | |

| | |
|--|---|
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) | |
| 1. Type of Well | OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER Water Injection Well |
| 2. Name of Operator | Amerada Hess Corporation |
| 3. Address of Operator | P.O. Box 840, Seminole, TX 79360 |
| 4. Well Location | Unit Letter <u>N</u> : <u>660</u> Feet From The <u>South</u> Line and <u>1980</u> Feet From The <u>West</u> Line Section <u>32</u> Township <u>19S</u> Range <u>37E</u> NMPM <u>Lea</u> COUNTY |
| 10. Elevation (Show whether DF, RKB, RT, GR, etc.) | |

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☒ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPERATIONS ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12.

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to MIRU pulling unit. Remove wellhead, install BOP & TOH w/pkr. TIH w/7" RBP set at +/- 3670' & press. test csg. to 700 PSI. Freepoint csg. & shoot squeeze holes. Circulate/squeeze prod./intermediate csg. annulus. Drill out cement & press. test csg. to 700 PSI. TOH w/RBP. Re-run pkr. set at +/- 3684' & press. test to 700 PSI, obtaining chart. Resume injecting water.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Roy L. Wheeler, Jr. TITLE Bus. Svc. Spec. II DATE 05/09/2002
TYPE OR PRINT NAME Roy L. Wheeler, Jr. TELEPHONE NO. 915-758-6778

(This space for State Use)

APPROVED BY PAUL F. KAUTZ TITLE PETROLEUM ENGINEER DATE MAY 14 2002
CONDITIONS OF APPROVAL, IF ANY: need chart on file

