## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## **MISCELLANEOUS NOTICES**

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INC	TENTION TO SH	HOOT OR	·
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INT	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING		
OTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL		
OTICE OF INTENTION TO DEEPEN WELL				
Monument, New				
	Place	Angust	26, 1936 Date	
IL CONSERVATION COMMISSION,				
anta Fe, New Mexico.				
ollowing is a notice of intentiton to do certain work as d				
Company or Operator Lease		No. 1	in SW4 SW	1
Sec. <b>53</b> , T. <b>19</b> , R. <b>37</b>	N. M. P. M., Mon	nument		Field
Loc County.				
8-5/8" 32# 8-thd. New Seamless of comented by the Halliburton Method with Casing and fittings will be tested stand undisturbed for thirty minutes.	d with 1200# pur	this well	at 2534 a	d to
Casing and fittings will be teste	easing was set in the 500 sacks.  Id with 1200# pure.  If no drop in pand the same to ed for thirty mis	this well  pressure  ressure res	at 2534' a and allowedults the co	i to
Casing and fittings will be teste stand undisturbed for thirty minutes. will then be drilled out of the casing applied and appowed to stand undisturb	easing was set in the 500 sacks.  Id with 1200# pure.  If no drop in pand the same to ed for thirty mis	this well  pressure  ressure res	at 2534' a and allowedults the co	i to
Casing and fittings will be teste stand undisturbed for thirty minutes. will then be drilled out of the casing applied and appowed to stand undisturb results the drilling will then be results.	easing was set in the 500 sacks.  In the sacks and with 1200# pure. If no drop in pand the same to sed for thirty mands.	n this well up pressure pressure res est of 1200# mutes. If	at 2534° a and allowed ults the compressure and arop in	i to
Casing and fittings will be teste stand undisturbed for thirty minutes. will then be drilled out of the casing applied and appowed to stand undisturb results the drilling will then be resulted and applied and approved	easing was set in the 500 sacks.  Id with 1200# pure.  If no drop in pand the same to ed for thirty mis	n this well up pressure pressure res est of 1200# mutes. If	at 2534 a and allowed ults the compressure of no drop in	i to
Casing and fittings will be teste stand undisturbed for thirty minutes. will then be drilled out of the casing applied and appowed to stand undisturb results the drilling will then be resulted and applied and approved	easing was set in the 500 sacks.  In the sacks and with 1200# pure. If no drop in pand the same to sed for thirty mands.	n this well  up pressure pressure res est of 1200# mutes. If	at 2534 a and allowed ults the compressure of no drop in	i to
Casing and fittings will be teste stand undisturbed for thirty minutes. will then be drilled out of the casing applied and appowed to stand undisturb results the drilling will then be resulted and applied and approved	easing was set in the 500 sacks.  In the 1200 pure of the part of the same to	n this well  up pressure pressure res est of 1200# mutes. If	at 2534 a and allowed ults the compressure of no drop in	i to
Casing and fittings will be teste stand undisturbed for thirty minutes. will then be drilled out of the casing applied and appowed to stand undisturb results the drilling will then be resulted and applied and approved	Amerada Petroposition  Amerada Petroposition  Position  Figure 1200# pure 15 no drop in pand the same teled for thirty mixed.	oleum Corpor Company or o	at 2534' a and allowed ults the compressure on odrop in	i to
Casing and fittings will be teste stand undisturbed for thirty minutes. will then be drilled out of the casing applied and appowed to stand undisturb results the drilling will then be resulted and applied and appowed.	Amerada Petroperation  Amerada Petroperation  By Addition  Send companies of the properation of the petroperation	oleum Corpor	at 2534' a and allowed ults the compressure of the pressure of	i to
Casing and fittings will be tested stand undisturbed for thirty minutes. Will then be drilled out of the casing applied and appowed to stand undisturbed results the drilling will then be resulted and applied and approved	Amerada Petrosenda compand the Sant Comp	oleum Corpor Company or o	at 2534' a and allowed ults the compressure on odrop in artion perator	i to

10R