State of New Mexico

Submit 3 Copies to Appropriate District Office	Energy, nerals	and Natural Re	ex-arces Departmen		Revised 1-1-59	
DISTRICT I P.O. Box 1980, Holbs, NM 88240	OIL CONS		N DIVISION	WELL AM NO.		
P.O. Box 2088 DISTRICT II P.O. Drawer DD, Artesia, NM 88210 DISTRICT III 1000 Rio Brazzos Rd., Aziec, NM 87410				30-025-05799		
				5. Indicate Type of Lease		
	TICES AND REPO					
	IOPOSALS TO DRILL RVOIR, USE "APPLI 2-101) FOR SUCH PF	CATION FOR PE	OR PLUG BACK TO RMIT"	A 7. Lease Name or Unit A	prement Name	
1. Type of Well: OL GAS WELL WILL X	1			C D - 111		
2. Name of Operator		OTHER	<u> </u>	Sarah Phillips 8 Well No.	Gas Com	
Amerada Hess Corporat	ion			1		
3. Address of Operator				9. Pool same or Wildox		
Drawer D, Monument, N	ew Mexico	88265		Eumont Yates 7	Rivers Queen	
	30 Pest From The _	South	Line and	2310 Pest Prom The	West Line	
Sertice 33	Township	19S Ra	37E	NMPM	Lea County	
		108 (Show whether	DF, RKB, RT, GR, etc.)	V///		
		3569				
		to indicate i		, Report, or Other Data		
NOTICE OF IN	IENTION TO:		Si	UBSEQUENT REPO	RT OF:	
PERFORM REMEDIAL WORK	PLUG AND AE	ANDON	REMEDIAL WORK	ALTER	ing casing	
TEMPORARILY ABANDON	CHANGE PLA	NS 🗌	COMMENCE DRILL	LING OPNS. DPLUG	AND ABANDONMENT	
PULL OR ALTER CASING		_	CASING TEST AND	CEMENT IOR		
OTHER:			OTHER:	Squeezed Eumont	perfs.	
12. Describe Proposed or Completed Opera	tions (Clearly state all)	pertinent details, an		ncluding estimated date of starting	алу proposed	
1/03 Thru 1/24/9	2					
MIRU DA & S 0il	Well Service	pulling un	it, removed w	ell head, installe	d BOP &	
TOH w/2-7/8" tbg	. Ran 3-1/2"	drlg. bai	ler & attempt	ed to knock out CI	BP at	
3650' w/no results P	ts. TOH. TI	H w/fishing	g tools & att	empted to recover ine & 1-1/4" wt. ba	fish	
Ran 5-3/4" magne	t & recovered	remainder	overeu sand i of junk. Ti	H w/5-7/8" bit, che	ar. ecked	
CIBP at 3650' &	pushed CIBP t	o 3740' &	TOH. Ran 6-5	/8" Arrow A-32 pkr	., set	
at 3461', loaded	csg. w/fresh	water, pro	ess. & est. i	ni, rate into Eumo	nt zone	
0-5/8" CSG. pert Rowland Trk num	5. Halliburt	on ran 6-5,	/8" cement re	tainer & set at 34! h water, set retain	53'.	
Now rund 11 k. pum	ped till odgir r	ecainer w/	20 0015. 11.62	n water, set retain	ner a	
				(Over)		
I hereby certify that the information above in true	and complete to the best of	any knowledge and b		C	1 (07 100	
SIGNATURE // E//	rulle, t	mu	Supv. Adm			
TYPEOR FRONT NAME R. L. WI	neeler, Jr.			T=12	PHONE NO. 393-2144	

CONDITIONS OF APPROVAL, IF ANY:

FEB 05'92

press. tested tbg. to 2500# & loaded & press. tested csg. to 500#. Held ok. Halliburton cement squeezed 6-5/8" csg. perfs. fr. 3506'-3736' w/300 sks. class "C" neat cement. Stung out of retainer, reversed out 13 sks., left 42.5 sks. in csg. & 244.5 ssks. in formation. WOC. TIH w/5-7/8" bit, checked cement top at 3441' & drld. cement, retainer at 3453' & cement to 3576' & circ. clean. Drld. cement to 3696'. Press. up on 6-5/8" csg. to 500# for 30 min. Held ok. Chart attached. Drld. hard cement fr. 3696' to 3740'. Drld. out CIBP at 3740', 10' cement & CIBP at 3750' & cement to 3757'. Circ. hole clean & TOH laying down tbg. & bit. Removed BOP & installed well head. RDPU & cleaned location. Well TA'd. PBD at 3757'.

Abandoned Eumont Yates 7 Rivers Queen zone for useable wellbore in North Monument Grayburg San Andres Unit.

Well name & number changed to North Monument Grayburg San Andres Unit Blk. 17 well No. 14.

rEB 03 1902

in the second se