

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-05799

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
AMERADA HESS CORPORATION

3. Address of Operator
DRAWER D, MONUMENT, NEW MEXICO 88265

4. Well Location
Unit Letter N : 330 Feet From The SOUTH Line and 2310 Feet From The WEST Line

Section 33 Township 19S Range 37E NMPM LEA County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3569' DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Abandon G.B. 8A + ☒
RECOMPLETE IN EUMONT ZONE

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-04-90 THRU 10-29-90

MIRU PULLING UNIT & INSTALLED BOP. RAN GAUGE RING & JUNK BASKET TO 3680' & TOH. DISPLACED 110 BBLs. OIL FR. WELL. RAN 6-5/8" CIBP & SET AT 3650'. CAPPED PLUG W/10' CEMENT. G/SA ZONE P & A'd. RAN 6-5/8" X 2-7/8" BAKER MD. R DBL. GRIP PKR. SET AT 3601' & TESTED CIBP TO 3000#. HELD OK. RELEASED PKR. & PRESS. 6-5/8" CSG. TO 500#. HELD OK. ACID ENGR. SPOTTED 5 BBLs. 15% ACID ACROSS EUMONT ZONE FR. 3460'-3601'. TOH W/PKR. RAN 4" PERFORATING GUN & PERF. EUMONT ZONE 6-5/8" CSG. FR. 3524'-3538' & FR. 3544'-3600' W/2 SPF FOR TOTAL OF 144 HOLES. RAN PKR. SET AT 3433' & PRESS. UP ON CSG. PERF. TO 1900# & BROKE DOWN PERFS. ACIDIZED EUMONT ZONE 6-5/8" CSG. PERFS. FR. 3524'-3600' W/1500 GAL. 15% NEFE HCL ACID. SWABBED WELL & TOH W/TBG. & PKR. RAN 2-7/8" TBG. SET OE AT 3581'. SWABBED WELL DRY, NO GAS & CI.

OVER

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. L. Wheeler, Jr. TITLE SUPV. ADM. SVC. DATE 11-20-90

TYPE OR PRINT NAME R. L. WHEELER, JR. TELEPHONE NO. 393-2144

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE NOV 27 1990

CONDITIONS OF APPROVAL, IF ANY: