NEW MEXICO OIL CONSERVATION CO MISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations

Indicate nature of notice by checking below:	
OTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL
OTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING
OTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL
OTICE OF INTENTION TO DEEPEN WELL	
Monument, Ner	Mexico June 30, 1936
L CONSERVATION COMMISSION, nta Fe, New Mexico. ntlemen:	Date*
ollowing is:a notice of intentiton to do certain work a	is described below at the
Amerada Petroleum Corporation Sarah Phillipsvou No.	
	, N. M. P. M., Monument Field
LeaCounty.	, N. M. P. M., MonutentField,
	ROPOSED PLAN OF WORK LES AND REGULATIONS OF THE COMMISSION
6-5/8" 20# 10-thd. New Electric and cemented by the Halliburton Method Casing and fittings willbe tested indisturbed for thirty minutes. If no be drilled out of casing and the case.	LES AND REGULATIONS OF THE COMMISSION
6-5/8" 20# 10-thd. New Electric and cemented by the Halliburton Method Casing and fittings willbe tested undisturbed for thirty minutes. If no be drilled out of casing and the same and sturbed for thirty minutes. If no be resumed.	welded casing was set in this well at 3759 of with 100 sacks of cement. I with 1200# pump pressure and allowed to stand drop in pressure results the cement will the test of 1200# again applied and allowed to stand drop in pressure results the drilling will to
6-5/8" 20# 10-thd. New Electric and cemented by the Halliburton Method Casing and fittings willbe tested and sturbed for thirty minutes. If no be drilled out of casing and the same and sturbed for thirty minutes. If no be resumed.	welded casing was set in this well at 3759 of with 100 sacks of cement. I with 1200# pump pressure and allowed to stand drop in pressure results the cement will the test of 1200# again applied and allowed to stand drop in pressure results the drilling will to
6-5/8" 20# 10-thd. New Electric and cemented by the Halliburton Method Casing and fittings willbe tested and sturbed for thirty minutes. If no be drilled out of casing and the same and sturbed for thirty minutes. If no be resumed.	welded casing was set in this well at 3759 of with 100 sacks of cement. I with 1200# pump pressure and allowed to standard of in pressure results the cement will the test of 1200# again applied and allowed to standard in pressure results the drilling will to
6-5/8" 20# 10-thd. New Electric and comented by the Halliburton Method Casing and fittings willbe tested and sturbed for thirty minutes. If no be drilled out of casing and the same and sturbed for thirty minutes. If no be resumed.	welded casing was set in this well at 3759. Welded casing was set in this well at 3759. With 1200# pump pressure and allowed to stand drop in pressure results the cement will the test of 1200# again applied and allowed to stand drop in pressure results the drilling will to drop in pressure results the drilling will be drop in pressure resul
6-5/8" 20# 10-thd. New Electric and cemented by the Halliburton Method Casing and fittings willbe tested undisturbed for thirty minutes. If no be drilled out of casing and the same undisturbed for thirty minutes. If no be resumed.	welded casing was set in this well at 3759. Welded casing was set in this well at 3759. With 1200# pump pressure and allowed to stand drop in pressure results the cement will the test of 1200# again applied and allowed to stand drop in pressure results the drilling will to drop in pressure results the drilling will to drop in pressure results the drilling will to drop in pressure results.
6-5/8" 20# 10-thd. New Electric and cemented by the Halliburton Method Casing and fittings willbe tested undisturbed for thirty minutes. If no be drilled out of casing and the same and sturbed for thirty minutes. If no be resumed.	welded casing was set in this well at 3759 of with 100 sacks of cement. If with 1200# pump pressure and allowed to stand drop in pressure results the cement will the test of 1200# again applied and allowed to stand drop in pressure results the drilling will to drop in pressure results the drilling will the drop in pressure results the dri