## NEW MEXICO OIL CONSERVATION COL. ASSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

EPORT ON BEGINNING DRILL	ING OPERATION	vs	REPORT O	ON REPAIRING	G WELL	
EPORT ON RESULT OF SHOOTII	NG OR CHEMICA	r	REPORT O	ON PULLING O	OR OTHERWIS	E
EPORT ON RESULT OF TEST OF SHUT-OFF	F CASING	žš	REPORT O	N DEEPENIN	G WELL	· · · · · · · · · · · · · · · · · · ·
EPORT ON RESULT OF PLUGGI	NG OF WELL					
	Monument	Now Mexic		ขื <b>อ</b> ेกง	ery 16, 1	937
IL CONSERVATION COMMIS	SSION,		Piace		D	ate
entlemen:						
ollowing is a report on the wo	ork done and th	e results obta	ained under th	ie heading no	ited ahove at	the
nerala Potrolam ar				hillie		2
Company or Operato			Lease	See the che charte of the	Well No	in t
NO SA	of Sec	<u> </u>	T. 19	, R	37	, N. M. P. I
Monument	Field,			Loc		Count
ne dates of this work were as i	follows:					
otice of intention to do the wo	rk was fwas no	#t1 submitted	on Form C-10	2 on Fe	brug y 15,	1937
-5/8" 20: 10-Thd. He by the Halliburton Met quing and fittings on	thod with K ere testod :	onding we 30 sacks.	e so <b>t i</b> n t General proc	this well	at 3760 :	nd comente
6-5/8" 20 10-Thd. He by the Halliburton Ket Casing and fittings we for thirty minutes. I the casing and the sanstand andisturbed for was then resumed.	w Jeanless thod with K ere testod o to drop in p to test of l thirty min	casing we to sacke. with 1.00; pressure i 1200; pung ates. No	e set in t pump pres esultedso pressure drop in pr	the cemen wasquin	obtained at 3760° at 110 word to t was ther applied at 150 at 110	nd comente stand und drilled or nd allowed the drilli
6-5/8" 20; 10-Thd. He by the Halliburton Met Casing and fittings we for thirty minutes. I the casing and the senstand andisturbed for	w Jeanless thod with K ere testod o to drop in p to test of l thirty min	casing we to sacke. with 1.00; pressure i 1200; pung ates. No	e set in t e par quay esaltedso erressure	the cemen wasquin	obtained at 3760° at 110 word to t was ther applied at 150 at 110	nd comente stand und drilled c
6-5/8" 20 10-Thd. He by the Halliburton Met Casing and fittings we for thirty minutes. I the casing and the san stand andisturbed for was then resumed.  tnessed by H. D. Joco;  Subscribed and sworn to befor	thod with Kere tested of lose test of left thirty mine	caping we be sacked with 1.00; pressure r 1200; purp ntes. No	part in the part of the part o	the cemen wasanin research re	obtained at 3760 st was ther applied at pulted so	nd comente stand und drilled o nd allowed the drilli
6-5/8" 20 10-Thd. He by the Halliburton Met Casing and fittings we for thirty minutes. I the casing and the sanstand andisturbed for was then resumed.  tnessed by H. D. Jocoj	thod with Kere tested of lose test of left thirty mine	cacing we so sucks.  with 1.00; pressure in 1200; purify ites. No Poss Dr	part in the part of the part o	or affirm thatect.	obtained at 3760° at 3760° at twee the information at 3760° at 1860°	and comenter  atomatical and a drilled a llowed the drilli  ol-pusher  Title  tion given above
6-5/8" 20 10-Thd. He by the Halliburton Met Casing and fittings we for thirty minutes. I the casing and the sanstand andisturbed for was then resumed.  tnessed by H. B. Joco;  Subscribed and sworn to befor day of Jelica.  Lewis A. Y.	thod with Kere tested of lose test of left thirty mine	canding we so sucks.  with 1.00; pressure re 1200; purify ites. No Poss Dr	parap prosection in the parapeter processing the processing processing processing processing presenting presen	or affirm thatect.  Parm Boss  Amerida P	obtained at 3760° at 3760° at twee the information at 3760° at 1860°	at nd und a drilled or al clowed the drilli ol-pusher Title tion given above