

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-05801

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Amerada Hess Corporation

3. Address of Operator

Drawer D, Monument, New Mexico 88265

4. Well Location

Unit Letter I : 1650 Feet From The South Line and 660 Feet From The East Line

Section 33 Township 19S Range 37E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3558' GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Cement Squeeze ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/23 Thru 1/02/92

MIRU DA & S Oil Well Svc. pulling unit, removed wellhead & installed BOP. TIH w/4-3/4" bit & checked btm. at 3878' & TOH. TIH w/5-1/2" Arrow A-32 pkr. testing at intervals & found leak between 3586' - 3625'. Set pkr. at 3566' & tested csg. to 500# for 30 min. Held ok. Ran 5-1/2" Halliburton cement retainer set at 3563'. Loaded tbq. & tested to 2000# & csg. to 500#. Halliburton cement squeezed 5-1/2" csg. leak fr. 3586' - 3625' & csg. perf. fr. 3691' - 3768' w/200 sks. class "C" neat cement. Reversed out 10 sks. & left 190 sks. in formation. TOH & WOC. Ran 4-3/4" bit & checked cement at 3553'. Drld. cement, retainer

(over)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. L. Wheeler, Jr. TITLE Supv. Adm. Svc. DATE 1/16/92

TYPE OR PRINT NAME R. L. Wheeler, Jr. TELEPHONE NO. 393-2144

(This space for State Use)

ORIGINAL SIGNED BY JERRY S. S. 1/16/92
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

JAN 29 '92

CONDITIONS OF APPROVAL, IF ANY:

& cement to 3709'. Tested 5-1/2" csg. & squeezed perfs. to 500# for 30 min. Tested ok. Drilled good cement fr. 3709' - 3871' & small shavings of metal & formation. TD at 3880'. Circ. clean & TOH w/tbg. & bit. Removed BOP & installed wellhead. RDPU & cleaned location. Well CI for use as usable wellbore in North Monument Grayburg San Andres Unit as BLK. 17 well #9.

Well #9.
as usable wellbore in North Monument Grayburg San Andres Unit as BLK. 17
Removed BOP & installed wellhead. RDPU & cleaned location. Well CI for use
of metal & formation to TD at 3880'. Circ. clean & TOH w/tbg. & bit.
min. Tested ok. Drilled good cement fr. 3709' - 3871' & small shavings
& cement to 3709'. Tested 5-1/2" csg. & squeezed perfs. to 500# for 30