

Santa Fe, New Mexico

1953 JAN 2 PM 3 55

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE**. If State Land submit 6 Copies

**AREA 640 ACRES
LOCATE WELL CORRECTLY**

Tres Oil Company Williams "A"
(Company or Operator) (Lease)
Well No. 1, in SE/SE ¼ of ¼, of Sec. 33, T. 19S, R. 37E, NMPM.
Monument Pool, Lea County.
Well is 330 feet from south line and 840 feet from east line
of Section 33. If State Land the Oil and Gas Lease No. is -
Drilling Commenced 12-3-57, 19.57 Drilling was Completed 12-31, 19.57
Name of Drilling Contractor Makin Drilling Company - rotary; Thomas Drilling Co.-cable
Address P. O. Box 1628, Hobbs, New Mexico; P.O.Box 2646, Hobbs, N.M.
Elevation above sea level at Top of Main Head 3,568 The information given is to be kept confidential until
~~not confidential~~ 19.

OIL SANDS OR ZONES

No. 1, from 3,840 to 3,847 No. 4, from 3,921 to 3,923
No. 2, from 3,870 to 3,875 No. 5, from _____ to _____
No. 3, from 3,885 to 3,888 No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.

No. 2, from.....to.....feet.

No. 3, from.....to.....feet.

No. 4, from.....to.....feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	24#	used	292	float			water shutoff
5 1/8"	15.5#	used	3,801	"			" " "

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/4"	8-5/8	302	200	plug		
7-7/8"	5 1/2"	3,811	200	"		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Natural well

Result of Production Stimulation

Depth Cleaned Out

LOG OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 3,811 feet, and from _____ feet to _____ feet.
 Cable tools were used from 3,811 feet to 3,923 feet, and from _____ feet to _____ feet.

PRODUCTION

Put to Producing 12-31-57, 19_____.
 OIL WELL: The production during the first 24 hours was 249 barrels of liquid of which 100% was
 was oil; _____% was emulsion; _____% water; and _____% was sediment. A.P.I.
 Gravity _____
 GAS WELL: The production during the first 24 hours was _____ M.C.F. plus _____ barrels of
 liquid Hydrocarbon. Shut in Pressure _____ lbs.
 Length of Time Shut in _____

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1,200		T. Devonian		T. Ojo Alamo
T. Salt	1,395		T. Silurian		T. Kirtland-Fruitland
B. Salt	2,400		T. Montoya		T. Farmington
T. Yates	2,760		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen			T. Ellenburger		T. Point Lookout
T. Grayburg	3,740		T. Gr. Wash.		T. Mancos
T. San Andres	3,921		T. Granite		T. Dakota
T. Glorieta			T. _____		T. Morrison
T. Drinkard			T. _____		T. Penn.
T. Tubbs			T. _____		T. _____
T. Abo			T. _____		T. _____
T. Penn.			T. _____		T. _____
T. Miss.			T. _____		T. _____

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	220		Surface sands and gravels				
220	1,200		Redbed				
1,200	1,395		Anhydrite				
1,395	3,740		Streaks of anhydrite lime and shale				
3,740	3,921		Lime and anhydrite and sand streaks				
3,921	3,923		Light tan porous dolomite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

_____ January 2, 1958 _____ (Date)
 Company or Operator Tres Oil Company Address P. O. Box 1628, Hobbs, N. M.
 Name John Adams Position or Title Agent