

Santa Fe, New Mexico CCC

1957 OCT 23 AM 8:30
WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

State Loc 373

(Company or Operator)

(Lase)

Well No. **2**, in **NW** $\frac{1}{4}$ of **NE** $\frac{1}{4}$, of Sec **34**, T **19S**, R **37E**, NMPM.

Forest

Pool.

144

County.

Well is 1980 feet from East line and 660 feet from North line.

of Section 34 If State Land the Oil and Gas Lease No. is B-274

Drilling Commenced **12:00 PM September 12,** 19**57** Drilling was Completed **October 1,** 19**57**

Name of Drilling Contractor..... **J.C. Crain Drilling Company**

Address 528 Wilson Building, Dallas, Texas

Elevation above sea level at Top of Tubing Head..... **3606** The information given is to be kept confidential until

19

No. 1, from 3562 to 3862 No. 4, from _____ to _____

No. 2, from to No. 5, from to

No. 3, from to No. 6, from..... to.....

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1. from to feet.

No. 2. from _____ to _____ ice: _____

No. 3. from to 1951

No. 4. from to feet.

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	28	New	347	-	-		Surface
5-1/2	14	New	3899	Float	-	3790 - 3800 3824 - 3836	Production
2-3/8	4.7	New	3710	-	-		Tubing

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
2-1/4	8-5/8	347	200	B.J. Service, Inc.		
7-7/8	5-1/2	3899	200	B.J. Service, Inc.		

(Record the Process used, No. of Ots. or Gals. used, interval treated or shot.)

Two stage fracture treatment thru perforations. 1st stage w/10,000 gals refined oil & 10,000 lbs sand. Injected 30 rubber balls & immediately frac treated same zone w/10,000 galls refined oil & 10,000 lbs sand.

Result of Production Stimulation.....Flowed back lead oil & then flowed 72 bbls of 36 gravity oil (new oil)
thru 24/64" choke in 6 hrs. GOR 1878.

Cleaned Out

Orig & 5cc: BOC, Hobbs; cc: State Land Offi cc
cc: FHR, HFD, File

