NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

Hodes deres occ

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is com-

	Indicate Nature of Report by Checking	Below	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)	
	February 28, 1955	Hobbe, New Maxico	
Following is a report on the world	k done and the results obtained under the heads	ng noted above at the	
(Company or O		(Lease)	
Prilling County	, Well No	in the	1
T 20-8 , R 37-8 , NMPM.,	Undesignated Pool,	<u>Las</u>	County
The Dates of this work were as follows:.	2-25, 2-27-55		•••••
Notice of intention to do the work (wa	s) (yes submitted on Form C-102 on	(Cross out incorrect words)	, 19 .55
and approval of the proposed plan (wa		(Cross dar moorest notas)	
DETA	ILED ACCOUNT OF WORK DONE AND R.	ESULTS OBTAINED	
	ef 10-3/4-inch casing and set		
Ran 6 joints, 267 feet, Comented with 200 saices	of 10-3/4-inch casing and set of 4% gel cement. Slurry weig	at 281 feet.	
Nan 6 joints, 267 feet, Commented with 200 saints 11:00 A.M., 2-25-55.	of 10-3/4-inch casing and set of 4% gel cement. Slurry weig iroulated 80 sacks.	at 281 feet. ht lk#. Plug on bottom at	
Nan 6 joints, 267 feet, Commented with 200 saints 11:00 A.M., 2-25-55.	of 10-3/4-inch casing and set of 4% gel cement. Slurry weig	at 281 feet. ht lk#. Plug on bottom at	
Nan 6 joints, 267 feet, Commented with 200 saints 11:00 A.M., 2-25-55.	of 10-3/4-inch casing and set of 4% gel cement. Slurry weig iroulated 80 sacks.	at 281 feet. ht lk#. Plug on bottom at	
Nan 6 joints, 267 feet, Commented with 200 saints 11:00 A.M., 2-25-55.	of 10-3/4-inch casing and set of 4% gel cement. Slurry weig iroulated 80 sacks.	at 281 feet. ht lk#. Plug on bottom at	
Nam 6 joints, 267 feet, Commented with 200 sakes 11:00 A.M., 2-25-55.	of 10-3/4-inch casing and set of 4% gel cement. Slurry weig iroulated 80 sacks.	at 281 feet. ht lk#. Plug on bottom at	
Han 6 joints, 267 feet, Comented with 200 sakes 11:00 A.M., 2-25-55.	of 10-3/4-inch casing and set of 4% gel cement. Slurry weig iroulated 80 sacks.	at 281 feet. ht lk#. Plug on bottom at	
Witnessed by Witnessed by Approved:	of 10-3/4-inch casing and set of 4% gel coment. Slurry weighted 80 sacks. CMP for 30 minutes. Test U.A. Humble will & Mefiniz (Company) I hereby certi	at 281 feet. ht lk#. Plug on bottom at	nd comple t
Commented with 200 sakes 11:00 A.M., 2-25-55. Commented with 800% Witnessed by (Name)	of 10-3/4-inch casing and set of 43 gel coment. Slurry weighted 80 sacks. CWP for 30 minutes. Test C.A. COMMISSION I hereby certito the best of Name.	ht life. Plug on bottom at No o rop in pressure. Tool Pasher (Title)	nd complet

(Date)