



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Nolen and Lane

(Company or Operator)

Cooper

(Lease)

Well No. 2, in NW 1/4 of NW 1/4, of Sec. 3, T. 20S, R. 37E, NMPM.

Monument

Pool,

Lea

County.

Well is 330' feet from North line and 4950' feet from East line

of Section 3. If State Land the Oil and Gas Lease No. is

Drilling Commenced May 4, 1955 Drilling was Completed May 12, 1955

Name of Drilling Contractor Bateman and Whitsitt

Address Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 3558' The information given is to be kept confidential until, 19

OIL SANDS OR ZONES

No. 1, from 3780 to 3918 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 37 to 50 feet. 13' water, sand

No. 2, from 920 to 940 feet. 20' water, sand

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10	40	S	200	Baker			
7 O. D.	20	S	3680	Baker			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	10	200	50	Halliburton		
9	7 O. D.	3680	600	Halliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

This is an old well and was deepened to 3918' and treated with 8000 lbs. sand and 8000 gallons petrofrac. It flowed 85 barrels per day clean oil. No water.

Result of Production Stimulation See above

Depth Cleaned Out

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
Cable tools were used from 3808 feet to 3918 feet, and from.....feet to.....feet.

Put to Producing.....**May 12**....., 19**55**

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

Southeastern New Mexico

T. Anhy.....	T. Devonian.....	T. Ojo Alamo.....
T. Salt.....	T. Silurian.....	T. Kirtland-Fruitland.....
B. Salt.....	T. Montoya.....	T. Farmington.....
T. Yates.....	T. Simpson.....	T. Pictured Cliffs.....
T. 7 Rivers.....	T. McKee.....	T. Menefee.....
T. Queen.....	T. Ellenburger.....	T. Point Lookout.....
F. Grayburg..... 3918'	T. Gr. Wash.....	T. Mancos.....
T. San Andres.....	T. Granite.....	T. Dakota.....
T. Glorieta.....	T.	T. Morrison.....
T. Drinkard.....	T.	T. Penn.....
T. Tubbs.....	T.	T.
T. Abo.....	T.	T.
T. Penn.....	T.	T.
T. Miss.....	T.	T.

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
3808 T. D.	3918 3918	110	Grayburg lime				

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

May 20, 1955 (Date)

Company or Operator Nolen and Lane

Name R. H. Nolen

Address Box 326, Hobbs, New Mexico

Position or Title Partner