State of New Mexico Energy, Programs and Natural Resources Department

Perm C-165 **Revised 1-1-59**

DISTRICCI P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088 Santa Fe, New Mexico 87504-2088

WELL	UT NO.
	30-025-05888
4	

	30-02	STATE FEE X 6. Sum Oil & Gas Lama No. 7. Lama Name or Unit Agreement Name NORTH MONUMENT G/SA UNIT BLK 22		
P.O. Desert DD, Artesia, NM 88210				
DESTRICT III 1000 Rio Sensos Rd., Aziec, NM 8741	6. State OE & Ges Le			
SUNDRY NO (DO NOT USE THIS FORM FOR I DIFFERENT REI (FORM	CK TO A 7. Lases Name or Uni			
I. Type of Well:				
OEL WILL WILL (8. Well No.	
AMERADA HESS CORPO	RATION		9. Pool same or Wild	7
POST OFFICE DRAWER	D. MONUMENT. N	FW MEXICO 88265	EUNICE MONU	i de la companya de
Well Location Unit Locat G: 1			ad 1980 Feet From Th	EAST Line
Unit Letter :	900 Pest Prom 156	NONTH LIBE	1500 PM PROB 15	
Section 4	Towaship	T20 Range R3	7 NMPM LE	A County
	10. Elevation	a (Show whether DF, RKB, RT, C	GR, etc.)	
	A POT	to Indicate Nature of N	Notice, Report, or Other D	ata
180	NTENTION TO:		SUBSEQUENT RE	
_	•			
RFORM REMEDIAL WORK	PLUG AND AB/	NDON REMEDIAL		TERING CASING
MPORARILY ABANDON	CHANGE PLAN	IS COMMENC	E DRILLING OPNS. 📙 PL	UG AND ABANDONMENT
ULL OR ALTER CASING		CASING TE	ST AND CEMENT JOB	
THER:		OTHER:	CASING TEST	X
FIND A RING GASKET A 6" x 600 SP00L A 08-08-92 THRU 08-0 08-10-92: TAGGED 128 JTS. 2-3/8" TE 127 JTS. 2-3/8" TE BBLS. WATER. PRES BETWEEN THE BOP AN MINS. HELD OK.	7-92 LL SERVICE PULL TO FIT WELLHEA ND BOP. 9-92: WELL CLO BOTTOM @ 3,865' G. TO 3,730'. G. SET PLUG @ SURED UP ON 5-1 ID WELLHEAD. IN	ED RODS AND PUMP. OSED IN. FOR 20' OF FILL. TOH W/BIT. RAN A 3,700'. STAR TOOL /2" CSG. TO 550# -	ATTEMPTED TO INSTAL EAD FROM 5-1/2" CSG. TOH W/2-3/8" TBG. 5-1/2" x 2-3/8" BAKE CIRCULATED THE 5-1/ LEAKED OFF. HAD A OL, PRESSURED UP ON C	L A BOP. COULD NOT INSTALLED A NIPPLE RAN A 4-3/4" BIT ON R LOC-SET RBP ON 2" CSG. CLEAN W/125 LEAK ON THE SPOOL SG. TO 570# FOR 37
			DOWN TO THE SURFACE PULLED AND LAID DOWN	

I hereby curtify that the info STAFF ASSISTANT 08-17-92 TELEPHONE NO. 505-393-2144 TYPE OR PRENT NAME

- TITLE -

(This space for State Line) INAL SIGNED BY JERRY SEXTON DISTRICT | SUPERVISOR

AUG 21'92 DATE -

APPROVED BY-CONDITIONS OF AFFROVAL IF ANY: LAID DOWN 2-3/8" TBG. RIGGED DOWN PULLING UNIT TO INSTALL MATTING BOARDS.

08-12-92: INSTALLED A CELLAR KIT AROUND WELLHEAD, INSTALLED MATTING BOARDS AND RIGGED UP PULLING UNIT. REMOVED WELLHEAD DOWN TO THE 5-1/2" CSG. SLIPS, RAN A SPEER W/A 4.805 GRAPPLE ON 12' N-80 SUB AND LATCHED ONTO 5-1/2" CSG. PULLED 80,000# ON CSG. PULLED SLIPS FREE FROM WELLHEAD, REMOVED SLIPS AND STACKED OUT 5-1/2" CSG. BACKED OFF AND REMOVED THE WELLHEAD FROM THE 7-5/8" INT. CSG. INSTALLED A NEW NATIONAL OILWELL WELLHEAD ON THE 7-5/8" INT. CSG. RAN A SPEER AND LATCHED ONTO 5-1/2" CSG. PULLED 55,000# ON 5-1/2" CSG. AND SET THE SLIPS. PULLED SPEER AND INSTALLED A NEW 6" x 900 WELLHEAD ON THE 5-1/2" CSG.

08-13-92: RAN A RETRIEVING HEAD ON 127 JTS. 2-3/8" TBG. AND LATCHED ONTO THE RBP. TOH W/TBG. AND PLUG. STAR TOOL LOADED THE CSG. W/20 BBLS. WATER. RAN A 4-3/4" BIT ON 130 JTS. 2-3/8" TBG., TAGGED UP ON FILL @ 3,856', BROKE CIRCULATION AND CLEANED OUT FILL TO PBD @ 3,885', RECOVERED SAND AND FORMATION. TOH W/TBG. AND BIT.

08-14-92: PICKED UP AND RAN 1 JT. 2-7/8" SALTA LINED TBG. AND 131 JTS. 2-3/8" TBG., SET 0.E. @ 3,866', SN @ 3,865'. RAN A 20 \times 125 \times RHBC-06-3-S-4 PUMP #A-1012 ON 112-3/4" RODS AND 41-7/8" RODS.

08-15-92 AND 08-16-92: CLOSED IN.

08-17-92: INSTALLED WELLHEAD CONNECTIONS AND CLEANED LOCATION. PUMPING.

24 HOUR TEST: 3 BOPD AND 12 BWPD

RECEIVED

AUG 2 0 1992

TO MORE THE COMME