NEW TICO OIL CONSERVATION CONTINUON Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

		Monumen t	, New Mexico		October 10	1936
OIL CONSERV			Pla	ace	Da	te
Gentlemen:	Santa Fe	e, New Mexico				
You are he	ereby notifie	d that it is our inte	ention to commence	the drilling of a	well to be known	as
Amerada Pe	troleum (Corporation		8 Well	No. 1 in	SW S
. a 5	m 2	Company or Oper	ator Lease M. P. M., Mon	ument	Field	Lea County.
of Sec	•		660 feet [1			
1 1	N.					
		_	of the West li			
		(Give locatio	n from section or oth	er legal subdivisio	n lines. Crossoutv	vrong directions.)
		If state land	the oil and gas lease	is No	Assignment I	
		If patented	land the owner is			
		Address				
		If governme	nt land the permitte	e is	·	
	<u> </u>	Address				
			s Amerada Pet			
		i I				
AREA	640 ACRES		Tulsa, Okl			
LOCATE W	ELL CORREC	We propose	to drill well with	drilling equipment	as follows:	
			Rotary.			
						f the Commission
is as follows:			sing and to land or			Sacks Cement
We propose to Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	dicated: Landed or Cemented	Sacks
We propose to Size of	use the foll	owing strings of ca	sing and to land or	cement them as in	Landed or Cemented	Sacks
We propose to Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth Minimum of lin red beds.	Landed or Cemented	Sacks Cement 200
We propose to Size of Hole 17½" 117 7-7/8"	Size of Casing 121 " 8-5/8" 6-5/8"	weight Per Foot 40# 32# 20#	New or Second Hand New Lapweld New Seamless New Seamless	Depth Minimum of 1 in red beds. Minimum of 3800° or or	Landed or Cemented 50' or 50' 2400' or thru	Sacks Cement 200 1 salt 500 100
We propose to Size of Hole 17½" 11 " 7-7/8"	use the foll Size of Casing 121 8-5/8* 6-5/82 the above plant or oductive of	Weight Per Foot 40# 32# 20# an become advisable	New or Second Hand New Lapweld New Seamless	Depth Minimum of 1 in red beds. Minimum of 3800° or on	Landed or Cemented 50' or 50' 2400' or three top of pay g or landing casin	Sacks Cement 200 1 salt 500 100
We propose to Size of Hole 17½" 11 1 7 7-7/8" If changes in that the first parts of the second s	Size of Casing 12½ 8-5/8 6-5/8 the above player of the above p	Weight Per Foot 40# 32# 20# an become advisable	New or Second Hand New Lapweld New Seamless New Seamless e we will notify you doccur at a depth o	Depth Minimum of lin red beds. Minimum of 3800° or on before cementing about 3800°.	Landed or Cemented 50' or 50' 2400' or thrutop of pay g or landing casin	Sacks Cement 200 1 salt 500 100 ng. We estimate
We propose to Size of Hole 17½" 11 ** 7-7/8** If changes in that the first padditional info	Size of Casing 12½ 8-5/8 6-5/8 the above player of the above p	Weight Per Foot 40# 32# 20# an become advisable	New or Second Hand New Lapweld New Seamless New Seamless e we will notify you doccur at a depth o	Depth Minimum of lin red beds. Minimum of 3800° or on before cementing about 3800°.	Landed or Cemented 50' or 50' 2400' or three top of pay g or landing casin	Sacks Cement 200 1 salt 500 100 ng. We estimate
We propose to Size of Hole 17½" 11 ** 7-7/8** If changes in that the first padditional info	Size of Casing 12½ 8-5/8 6-5/8 the above player of the above p	Weight Per Foot 40# 32# 20# an become advisable	New or Second Hand New Lapweld New Seamless New Seamless e we will notify you doccur at a depth o	Depth Minimum of lin red beds. Minimum of 3800° or on before cementing about 3800°.	Landed or Cemented 50' or 50' 2400' or thrutop of pay g or landing casin	Sacks Cement 200 1 salt 500 100 ng. We estimate
We propose to Size of Hole 172" 11 17 7-7/8" If changes in that the first padditional info	Size of Casing 12½ 8-5/8 6-5/8 the above player of the above p	Weight Per Foot 40# 32# 20# an become advisable	New or Second Hand New Lapweld New Seamless New Seamless e we will notify you doccur at a depth o	Depth Minimum of I in red beds. Minimum of 3800° or on before cementing about 3800°. Sincerely yours, merada Petro. By It Stud	Landed or Cemented 50' or 50' 2400' or three top of pay g or landing casing fact.	Sacks Cement 200 1 salt 500 100 ng. We estimate
We propose to Size of Hole 17½" 11 '' 7-7/8" If changes in that the first padditional info	Size of Casing 12½ 8-5/8 6-5/8 the above player of the above p	Weight Per Foot 40# 32# 20# an become advisable	New or Second Hand New Lapweld New Seamless New Seamless e we will notify you doccur at a depth o	Depth Minimum of I in red beds. Minimum of 3800° or on before cementing about 3800°. Sincerely yours, merada Petro. By A June Position Farm	Landed or Cemented 50' or 50' 2400' or three top of pay g or landing casing feet. General Corporation of Co	Sacks Cement 200 1 salt 500 100 ng. We estimate
We propose to Size of Hole 17½ 11 7-7/8 If changes in that the first padditional info	Size of Casing 12½ 8-5/8 6-5/8 the above player of the above p	Weight Per Foot 40# 32# 20# an become advisable or gas sand should	New or Second Hand New Lapweld New Seamless New Seamless e we will notify you doccur at a depth of the control of the cont	Depth Minimum of I in red beds. Minimum of 3800° or on before cementing about 3800° Sincerely yours, merada Petro By June Position Farm Send communication	Landed or Cemented 50' or 50' 2400' or three top of pay g or landing casing fact.	Sacks Cement 200 1 salt 500 100 ng. We estimate