

FIELD Furness River, Quinn	OPERATOR Himerca Hess Corp	DATE 4/27/76
LEASE E.S. Adkins	WELL NO. 3	LOCATION 330' FSL, 330' FWL, Sect. 5, T20-S, R 37-E

13 3/4" casing set at 300' with 300 sx. * _____ cement
Hole size 17 1/2" - Cement Circulated

* 250 sx. 50% Pozmix + 50% Reg. cement mixed 2% Gel + 50 sx. Incor cement
total 300 sx.

9 5/8" casing set at 2490' with 1850 sx of * _____ cement
Hole size 12 1/4" - Cement Circulated

* 1800 sx 50% Pozmix + 50% reg. cement + 50 sx. Incor cement, total 1850 sx.

9 5/8" csg. perf at 2490'-3399'

DN Collar At 3399'

3648' Liner top

7" casing set at 3690' with 100 sx of reg cement
Hole size 8 3/4" Calc. cement top @ 3266'

5 1/2" liner perf 5179-5220'
Cast Iron Retainer At 5275'

5 1/2" liner perf 5590-5623' (squeezed perfs 5590-5623 w/75 sx s/o set cement)

Cast Iron Retainer At 5650'

5 1/2" liner perf 5670-5710' (squeezed perfs 5670-5710 w/75 sxs. s/o set cement)

5 1/2" liner set at 5714' with 175 sx of reg. cement
Total Depth _____' Hole size 6 7/8" Calc. cement top @ 4200'

Total Depth 5210'