

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

The Ohio Oil Company

Hobbs, New Mexico

Company or Operator

Address

Bertha Barber

Well No. 6 in NW 1/4 of Sec. 5, T. 20 S

Lease

R. 37 E, N. M. P. M. Monument Field, Lea County.

Well is 1980 feet south of the North line and 660 feet west of the East line of Section 5

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Bertha J. Barber, Address Abilene, Texas

If Government land the permittee is, Address

The Lessee is, Address

Drilling commenced November 16, 1936. Drilling was completed Dec. 27, 1936

Name of drilling contractor Noble Drilling Company, Address Tulsa, Oklahoma

Elevation above sea level at top of casing 3557 feet.

The information given is to be kept confidential until 19.

OIL SANDS OR ZONES

No. 1, from 3820 to 3890 No. 4, from to
No. 2, from 3820 to 3890 No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"	40 ¹ / ₂			141	Reg			
9 5/8"	36 ¹ / ₂			1105	Float			
7"	24 ¹ / ₂			3817	Float			
2 1/2"	6.5	tubing		3866				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2"	13"	141	125	Halliburton	10	40
11	9 5/8	1105	500	"	10	40
9 3/4	7"	3817	400	"	10	40

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Dowell XX	2000	12/26/36		

Results of shooting or chemical treatment After acid treated 75 barrels per hour thru 1" choke
w/1 1/2 million cu ft of gas

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3890 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing December 27, 1936
The production of the first 24 hours was 25 barrels of fluid of which 100 % was oil; %
emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Jack Clark, Driller Bruce Harp, Driller
R. C. Lindsey, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 5.

day of Jan., 1936

Notary Public.

My Commission expires 10-24-37

Hobbs, New Mexico 1/4/37

Name

Position Sup't

Representing The Ohio Oil Company

Address P.O. Box 1607, Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	60	60	Caliche & sand
60	155	95	Red beds
155	520	365	Red beds & rock
520	786	266	Red beds & Shells
786	938	152	Red beds & rock
938	1024	86	Green sand-shale
1024	1055	31	Red rock
1055	1150	95	Anhy
1150	1646	496	Potash-salt-anhy
1646	1893	247	Salt-anhy streaks
1893	2145	252	Salt-anhy shell
2145	2205	60	Salt-anhy
2205	2243	38	Anhy
2243	2345	102	Anhy-gyp streaks
2345	2373	28	Lime-anhy shell
2373	2411	38	Anhy-gyp
2411	2479	68	Anhy-broken lime
2479	2551	72	Lime-anhy-gyp streaks
2551	2585	34	Broken lime
2585	2596	11	Heavy gas
2596	2604	8	Anhy-gyp-lime
2604	2626	22	Lime
2626	2675	49	Broken lime-gas
2675	2755	80	Broken lime
2755	2795	40	Broken lime-brown
2795	2824	29	Broken lime-grey
2824	2853	29	Lime-gyp
2853	2871	18	Grey lime
2871	2899	28	Broken lime
2899	2917	18	Grey lime-anhy
2917	2930	33	Grey lime
2930	2980	30	Lime
2980	3005	25	Grey lime
3005	3026	21	Broken lime
3026	3042	16	Lime
3042	3079	37	Broken lime
3079	3086	7	Grey lime
3086	3090	4	Lime gas
3090	3110	20	Broken lime
3110	3135	25	Grey lime
3135	3175	40	Broken lime
3175	3206	31	Lime
3206	3269	63	Broken lime
3269	3325	56	Lime show of gas
3325	3377	52	Broken lime
3377	3419	42	Broken lime-brown
3419	3428	9	Lime
3428	3475	47	Broken lime
3475	3546	71	Lime
3546	3595	49	Broken lime
3595	3627	32	Lime
3627	3664	37	Broken lime
3664	3751	87	Broken lime oil odor
3751	3765	14	Lime
3765	3792	27	White lime
3792	3805	13	Broken lime
3805	3825	20	Brown & grey lime oil odor
3825	3832	7	Brown & grey lime
3832	3853	21	Grey lime
3853	3874	21	Broken lime
3874	3890	16	Grey brown lime