

UP IN TANK PETROLEUM

LUMONT QUEEN

FIELD: EUNICE MONUMENT GB-S.

LEASE: BRITT "B" WELL NO. 2

DATE: _____ SPUDDED: 3/27/53 COMP. 5/29/53

ELEV: KB @ 3561' (12' above GL)

LOCATION: UNIT LETTER N, 330' FSL & 1650' FWL of

SECTION 5, T-20-S, R-37-E,

LEA COUNTY, NEW MEXICO

TA'd
Condition

Found 5 1/2" csg leak in 1st coilar from surface. Pull and replace 6 jts csg.

RBP set at ~3100' w/ sand on top

13 3/8 " 48 # CSG. at 604' w/ 550 SX.

17 1/4 " HOLE TOC @ surface (circ.)

Tbg Detail: 34' of 2 3/8", 4.7", J-55, EUE, 8R +bg
Baker Model "L" Sliding Sleeve w/ 1.875" "F" Profile @ 3261'
27' of 2 3/8", 4.7", J-55, EUE, 8R +bg
On/Off Tool @ w/ 1.81" "F" Profile @ 3288' (Probably Guiberson XL)
Guiberson Uni-Pkr VI @ 3289'

Cut csg @ 2865'. Pull csg. Replace 249' of 5 1/2" csg. Ran csg w/ Baash-Ross csg bowl

8 5/8 " 24.28 32 # CSG at 2999' w/ 1500 SX. (1000 SX w/ 3% gel & 500 SX new)

11 " HOLE TOC @ 850' (by T.S.)

0-284' → J-55, 24"
2104'-2396' → H-40, 28"
2396'-2999' → J-55, 32"

Queen Perfs: 3155'-60', 3170'-82', 3190'-3200', 3235'-45', 1 spf

Grayburg Perfs: 3350'-65', 1 spf

CIBP @ 3490'

Perfs: 3509', 3520'-22', 3525'-27', 3530'-33', 3535'-62', 1 spf

Cmt Ret @ 3593'. Pump 700 ex Class "C" thru retainer. TOC @ 2058'

Csg Leaks 3635'-3932'

CIBP @ 4000' w/ 10' cmt on top

Csg Leaks 4021'-31'

Cmt Ret @ 5078' w/ 40' cmt on top

Paddock Perfs: 5175'-5230', 4 spf

CIBP @ 5354' w/ 10' cmt on top

Blinebry Perfs: 5665'-10', 4 spf

Drill out FC & cmt to 5700' 5 1/2 " 14.55 # CSG. at 5710' w/ 600 SX. (300 SX w/ 3% gel & 300 SX new)

7 7/8 " HOLE TOC @ 4195' (by TS)

0-5281' → J-55, 14"
5281'-5710' → J-55, 14.5"

TO 5711'
PBD