

UNION TEXAS PETROLEUM

EUMONT QUEEN

FIELD: EUNICE MONUMENT GB-SA

LEASE: BRITT "B" WELL NO. 2


DATE: _____ SPUDED: 3/27/53 COMP. 5/29/53

ELEV: KB @ 3561' (12' above GL)

LOCATION: UNIT LETTER N, 330' FSL & 1650' FWL of
SECTION 5, T-20-S, R-37-E,
LEA COUNTY, NEW MEXICO

Present
Condition

Found 5 1/2" csg leak in 1st collar from surface. Pull and replace 6 jts csg.



13 3/8" 48 # CSG. at 604' w/ 550 SX.

17 1/4" HOLE TOC @ surface (circ.)

Tbg Detail: 34' of 2 3/8", 4.7", J-55, EUE, 8R +bg
 Baker Model "L" Sliding Sleeve w/ 1.875" "F" Profile @ 3261'
 27' of 2 3/8", 4.7", J-55, EUE, 8R +bg
 On/Off Tool @ w/ 1.81" "F" Profile @ 3288' (Probably Guiberson XL)
 Guiberson Uni-Pkr VI @ 3289'

Cut csg @ 2865'. Pull csg. Replace 249' of 5 1/2" csg. Ran csg w/ Baash-Ross csg bowl

8 5/8" 24, 28, 32 # CSG at 2999' w/ 1500 SX. (1000 SX w/ 3% gel & 500 SX neat)

11" HOLE TOC @ 850' (by T.S.)

0-2184' → J-55, 24"
 2104'-2396' → H-40, 28"
 2396'-2999' → J-55, 32"

Queen Perfs: 3155'-60', 3170'-82', 3190'-3200', 3235'-45', 1 spf

Grayburg Perfs: 3350'-65', 1 spf

CIBP @ 3490'

Perfs: 3509', 3520'-22', 3525'-27', 3530'-33', 3535'-62', 1 spf

Cmt Ret @ 3593'. Pump 700 SX Class "C" thru retainer. TOC @ 2058'

Csg Leaks 3635'-3932'

CIBP @ 4000' w/ 10' cmt on top

Csg Leaks 4021'-31'

Cmt Ret @ 5078' w/ 40' cmt on top

Paddock Perfs: 5175'-5230', 4 spf

CIBP @ 5354' w/ 10' cmt on top

Blaine Perfs: 5665'-90', 4 spf

Drill out 5 1/2" 14, 15.5 # CSG. at 5710' w/ 600 SX. (300 SX w/ 3% gel & 300 SX neat)

7 7/8" HOLE TOC @ 4195' (by TS)

0-5281' → J-55, 14"
 5281'-5710' → J-55, 15.5"

TD 5711'

PBTD _____