State of New Mexico Ens. Minerals and Natural Resources Department

Perm C	-149
Royland	1-1-00

P.O. Box 1980, Hothe, NM 88240 OIL CONSERVAT P.O. Box 1980, Hothe, NM 88240		JFI NO.
DISTRICT II Santa Fle. New Mexico 87504-2088		
P.O. Deswer DD, Artesia, NM 88210	3. India	STATE FEE X
DISTRICT III 1000 Rio Bresos Rd., Aziec, NM 87410	6. State	Oli & Ges Lesse No.
SUNDRY NOTICES AND REPORTS ON V	ELLS /////	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEF DIFFERENT RESERVOIR. USE "APPLICATION FOR (FORM C-101) FOR SUCH PROPOSALS.)	EN OR PLUG BACK TO A 7 1	ne Name or Unit Agreement Name
1. Type of Well: OR GAS WELL X OTHER	L.	M. Lambert
2. Name of Operator	E. Wel	1 No.
Amerada Hess Corporation Address of Operator	9. Poo	i name or Wildcet
Drawer D, Monument, New Mexico 88265	Mor	nument McKee Ellenburger
35	Range 37E NMPM Nor DF, RKB, RT, GR, etc.) 71' DF	Feet From TheNorthLine
11. Check Appropriate Box to Indica	_	
NOTICE OF INTENTION TO:	SUBSEQU	JENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TEST AND CEMENT J	oe 🗌
		G/SA Zone X
12. Describe Proposed or Completed Operations (Clearly state all pertinent detail work) SEE RULE 1103. 11-6 to 11-24-80 Refer to C-103 (Notice MIRU X-Pert pulling unit. Installed BOP tbg. at 9273'. TOH w/304 jts. 2-3/8" tbg "B" bridge plug & set at 5510'. Set 4-1/for 10 min. TOH w/pkr. Spotted 300# 20/Checked sand at 5473'. Ran 6-5/8" Arrow rate at 3 BPM, 1800#. TOH w/pkr. Ran HO Halliburton squeezed Grayburg San Andres w/100 sks. Class "C" cement mixed 0.4% Hasks. below retainer in 6-5/8" csg., circ. retainer. WOC-G/SA Zone Abandoned. Ran 5' of cement to top of retainer at 3570'. tested csg. w/850#. Held OK. Circ. sand Swabbed & returned well to status of flow	e of Intention) filed a laid down l-1/2" tbg. & found tbg. not comply large at 5458'. Present at 5458'. Present at 3570'. Low 200 6-5/8" EZE drill comply lad A. Squeezed 32 sk out 13 sks., 5' of cere at 5510'. Tothing gas well on 11-24-	McCullough jet cut 2-3/8" pletely cut. Ran Arrow type ss. up on BP to 1100# & held sh water on top of BP. aded back side & established ement retainer set at 3570'. perf. fr. 3703' - 3713' s. into formation, left 21 ment in 6-5/8" csg. above op of cement at 3565'. Drld cement to 3797'. Press. w/RBP. Re-ran 2-3/8" tbg.,
(K f. Wheeler ()	Supv. Adm. Svc.	3-8-89
D. I. Itheolog. In	IIILE	505 TELEPHONE NO. 393-2144
(This space for State Use ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR		MAR 1 3 1989

APPROVED BY --

Producing fr. McKee Ellenburger 4-1/2" csg. perfs. fr. 9568' - 9786'.

RECEIVED

MAR 1 0 1989

OCD HOBBS OFFICE