

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) Dual complete	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hebbs, New Mexico
(Place)

February 7, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Amerada Petroleum Corporation **L. M. Lambert** Well No. **7** in **H**
(Company or Operator) (Unit)
NE **NE** **6** **20-S** **3 1/2-E** **Monument Blinebry** Pool
(40-acre Subdivision) 1/4 of Sec. T. R. NMPM.,
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plan to pull rods, pump and tubing. Run Gamma Ray Neutron log. Squeeze 8-3/4" open hole from 5715' to 5730' with 75 sacks cement. Drill out, subject to logs. Perforate 7" OD casing in Blinebry zone and San Angelo zone, subject to logs. Run Brown packer, sliding sleeve and tubing. Swab test lower perforations and treat with 500 gals. acid and if necessary sand oil frac with 10,000 gals. crude oil and 10,000 lbs. sand. Open sleeve and set blanking plug and treat San Angelo perforations with 500 gals. acid. Pull tubing and perforate Paddeok zone, subject to logs. Set bridge plug and acidize Paddeok zone with 500 gals. 15% H.E. acid. Sand oil frac perforations with 10,000 gals. oil and 10,000 lbs. sand. Run 2 strings 2-3/8" OD tubing and dual complete in the Paddeok and Blinebry zones.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Amerada Petroleum Corporation
Company or Operator

By.....
Position..... **District Superintendent**
Send Communications regarding well to:

Amerada Petroleum Corporation
Name.....
Address..... **P. O. Box 668 - Hebbs, New Mexico**