

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) <b>Recomplete as dual</b>	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Monument, New Mexico

August 30, 1962

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Amerada Petroleum Corporation** **L. M. Lambert**

Well No. **8** in **B**

(Company or Operator)

(Unit)

**NW** **NE** **6** **20-S** **37-E** **Monument-Blinbry** Pool  
(40-acre Subdivision) 1/4 of Sec. T. R. NMPM.

**Lea**

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Plan to pull rods, pump and tubing. Run cement bond log, squeeze 6-1/4" open hole from 5665' to 5715' with 75 sacks Incon cement and drill out to 5679'. Perforate open hole in Blinbry zone from 5665' to 5678' with one bullet shot per foot, 5" OD liner in San Angelo zone from 5583' to 5615' with two bullet shots per foot and 5" OD liner in Paddock zone from 5198' to 5216' with two bullet shots per foot. Run tubing and packer and test Blinbry open hole from 5665' to 5678' and if necessary acidize with 250 gals. acid. Pull tubing and run retrievable bridge plug with packer and set at approx. 5630' and swab test the San Angelo perforations from 5583' to 5615'. Acidize with 500 gals., swab test, and sand oil free with 10,000 gals. crude oil and 10,000# sand and swab test. Pull bridge plug up and reset at approx. 5300'. Test Paddock zone and if necessary acidize with 500 gals., swab test. Pull bridge plug and tubing. Run one string 2-3/8" OD tubing with 2-1/16" tubing from top of liner to Blinbry zone and one string 2-3/8" tubing with 1-1/4" tubing from top of liner to Paddock zone. **Recomplete as a dual.**

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

**AMERADA PETROLEUM CORPORATION**

Company or Operator

By *[Signature]*  
Position **Asst. District Superintendent**

Send Communications regarding well to:

Name **Amerada Petroleum Corporation**

Address **Drawer "D", Monument, New Mexico**