

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-70

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name L. M. Lambert
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 11
4. Location of Well UNIT LETTER <u>B</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>6</u> TOWNSHIP <u>20S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Eunice Monument G/SA
11. Elevation (Show whether DF, RT, CR, etc.) 3573' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
		OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

May 13, 1985 to May 24, 1985 - Pulled rods, pump & tbg., perforated 6-5/8" csg. opposite Grayburg San Andres zone selectively w/2 SPF as follows: 3520', 3522', 3524', 3526', 3534', 3550', 3552', 3562', 3569', 3572', 3578', 3581', 3583', 3585', 3587', & 3590', total of 32 shots. Set retrievable bridge plug in 6-5/8" csg. at 3692' & set pkr. at 3597'. Acidized Grayburg San Andres zone thru 6-5/8" csg. perf. fr. 3520' to 3590' w/2000 gal. 15% NF HCl acid mixed w/5% checkersol using ball sealers as diverter. Swabbed load. Recovered bridge plug. Ran hydrostatic bailer & cleaned out fill inside 6-5/8" csg. to 3635'. Recovered est. 10 gal. formation sand. Ran pkr. & tbg. & set pkr. at 3599' & acidized Grayburg San Andres zone thru 6-5/8" csg. perf. fr. 3606' to 3629' w/500 gal. 15% NE HCl acid mixed w/5% checkersol using ball sealers as diverter. Swabbed load. Pulled tbg. & pkr., re-ran tbg., pump & rods and resumed production.

No test reported.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. B. Seay TITLE Supv. Adm. Ser. DATE 5-20-85

APPROVED BY Eddie W. Seay TITLE Oil & Gas Inspector DATE MAY 22 1985

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 21 1985

O.C.D.
HOBBS OFFICE