

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name L. M. Lambert
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 11
4. Location of Well UNIT LETTER <u>B</u> , <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>6</u> TOWNSHIP <u>20E</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat Eunice Monument G/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3573' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plan to pull rods, pump & tbg., perforate 6-5/8" csg. opposite Grayburg San Andres zone selectively from 3520' to 3595' w/2 SPF. Set retrievable bridge plug in 6-5/8" csg. at 3605', set pkr. at 3600' & test bridge plug, re-set pkr. at 3500' & acidize G/SA zone thru 6-5/8" csg. perf. fr. 3520' to 3595' w/2000 gal. 15% acid w/additives using ball sealers as diverter. Swab load. Re-set retrievable bridge plug at 3635', re-set pkr. at 3600' & acidize G/SA zone thru 6-5/8" csg. perf. fr. 3606' to 3629' w/500 gal. 15% acid w/additives using ball sealers as diverter. Swab load. Pull tbg., pkr. & bridge plug. Re-run tbg., pump & rods and resume production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. B. Miles TITLE Supv. Adm. Ser. DATE 5-9-85

APPROVED BY [Signature] TITLE [Signature] DATE 1985

CONDITIONS OF APPROVAL, IF ANY: