

DST 6420-6542', open 1 hr., Rec. 10' drlg fluid w/trace of oil.

DST 7210-7303', open 2 hrs, 10 mins. GTS 45 mins. Fair blow of gas, decreased to a very faint blow at finish of test.

DST 7485-7550', open 2 hrs, GTS 8 mins, weak blow. Rec 255' sulphur wtr, 15' DF.

DST 7560-7620', open 3 hrs, GTS 10 mins, good blow of gas, decreased to weak blow at end of test, rec. 450' free oil & 270 HO&GCDF.

DST 7710-7760', open 3 hrs. Rec 90' HO&GCDF.

DST 9695-9757', open 95 mins. Rec. 30' of DF.

DST 9760-9800', open 2 hrs 40 mins, flwd gas @ a calculated rate of 4600 MCF, Prod. estimated @ 5 to 7 bbls dist. per hr.

DST 9895-9926', open 2 hrs. Rec 30' of SGCDF, 2160' salt water.

DST 10,050-10,095', open 2 hrs. Rec 30' DF, 3470' salt water.

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = \int_{\mathbb{R}^n} u \Delta u dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

• $\frac{1}{2} \frac{d}{dt} \int_{\mathbb{R}^n} |u|^2 dx = - \int_{\mathbb{R}^n} |\nabla u|^2 dx$ (conservation of energy)

•