NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

			of the Comm	nission. Submit in	QUINTUPLIC	ATE.	ruics and regi
LOCA	AREA 640 AC TE WELL CO	RES RRECTLY					
	Gulf Of		t i on				3
	9	(Company or Ope		6	T.	20-S R	
							•
						Lea	
						feet from	
Drilling Con	nmenced	May	17	19 54 Drillin	ng was Completed	L	July 8, , 19
Name of Dr	illing Contra	ctor	L	offland Bro	s. Drilling	g Co.	
Address			1005 E	lectric Blo	g., Fort	orth, Texas	
Elevation ab	ove sea level	at Top of Tubin	g Head 356	41	The in	formation given is to	be kept confidentia
	·•		, 19				-
			0.7	* GANDO OD 0	· O D T T T T T T T T T T T T T T T T T T		
	ETERT			L SANDS OR Z			
						to	
						to	
No. 3, from		t	0	No. 6	5, from	to	
			IMPOF	RTANT WATER	REANTS		
nclude data	on rate of w	ater inflow and	elevation to which				
						fee t	
						feet.	
						feet.	
						feet	
No. 4, Irom			to			leet.	
				CASING RECO	RD		
SIZE	WEIGH PER FO			KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
					T CLEAR THOM	LEGIONATIONS	FURFUSE
13-3/8" 9-5/8"	4 8 _i	# New New	280		 -		
7-5/8"	26.4		34861				
5-1/2"	15.50		18031	1			
			MUDDING	AND CEMENT	THE DECEMBE		
SIZE OF	SIZE OF	AND THE PARTY OF T			ING RECORD		
HOLE	CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	G	RAVITY	AMOUNT OF MUD USED
18"	13-3/8"	2951	325	HOWCO			
12-1/4"	9-5/8"	23401	1015	HOWCO			
8-3/4"	7-5/8"	34981	170	HOWCO			
6-3/4"	5-1/2"	52491	200	HOWCO	<u> </u>	l	· · · · · · · · · · · · · · · · · · ·
			RECORD OF P	PRODUCTION A	AND STIMULAT	TION	
		(Record th	ne Process used, No	. of Qts. or Gal	s. used, interval	treated or shot.)	
		•••••••••••••••••••••••••••••••••••••••			***************************************	•••••••••••••••••••••••••••••••	
		···					
***************************************	•••••••••••		•	•	•••••••	•	
•••••••	·····						
lesult of Pro	duction Stim	ulation					
Court Of 110	aacton Juli		•••••••••••••••••••••••••••••••••••••••	***************************************	••••••	•••••••••	••••••

Depth Cleaned Out

R WORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary too	ls were us	ed from	O feet t	。 52501	feet, and	d from		feet to	feet.	
Cable tools	s were use	d from	feet t	o	feet, and	d from	····	feet to	feet.	
				PRODUC	TION					
Put to Pro	ducing		July 27							
OIL WEL	L: The	production	during the first 24 ho	urs was 261	4	barr	els of liqu	id of which10	O ~ was	
	was	oil;	% was e	mulsion;		% water;	and	% ч	vas sediment. A.P.I.	
	Grav	/i ty	38.1							
GAS WEI	L: The	product:or	during the first 24 ho	urs was		I.C.F. plu	.s		barrels of	
			rbon. Shut in Pressure.							
Length of	•	•								
			ELOW FORMATION		ORMANO	E WITH	GEOGR	APHICAL SECTION	ON OF STATE).	
FLEE	SE IND	CALE B	Southeastern New 1		Olemanic	/13 ((1111	QEOUT.	Northwestern 1		
T. Anhy.		1020	Т.	Devonian			Т.	Ojo Alamo		
			т.	Silurian			T.	•		
		21901	T							
		23701	T.	•						
			Т.	•			_			
			Т.					Point Lookout		
_			T.	=						
								T. Dakota		
			•					T. Morrison		
			T.							
				• • • • • • • • • • • • • • • • • • • •						
			_				_			
			T	•						
T. Miss.			Т	FORMATIO			1.			
		Thickness					Thickness			
From		in Feet	Format		From	То	in Feet		mation	
0	12		Distance from	•		3367		Lime Lime and G	man n	
	651		Drive Bushin	ig to around		3387 5250		Lime	/psuma	
	790		Red Bed			72.70		ALLING		
	1022	1	Red Bed and Re	ed Rock		5238		Plugged Bac	ck Total Depth	
	1125		Red Bed and Ar					,		
	1320		Salt and Anhyo							
	1708		Red Bed			,		I		
	2115		Salt and Anhyo		li .					
	2269		Anhydrite and						•	
	2335		Anhydrite, Lir	ne & Gypsum	H				,	
	2348		Lime							
	2351		Anhydrite	ಳೊಹ ಡ						
	2409 246 7		Anhydrite and Lime and Anhyd							
	2525		Anhydrite and							
	2583		Anhydrite and							
	2753 Tile, Sand & Anhydrite									
	2816 Lime and Anhydrite									
	2924 Dolomite and Anhydrite									
	3040	C40 Anhydrite and Sand								
	3156	Sand and Dolomite								
	3214		Dolomite, Sand	a annydrite						
	3272		Sand and Dolor	id to						
	3330	1	haud aug boro	: 12 0 G	1			ļ.,		

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a	complete and correct record of the well and all work done on it so far				
as can be determined from available records.					
	September 7, 1954 (Date)				
Company or Operator Gulf 911 Corporation	Address Box 2167, Hobbs, New Mexico				
" 27 Janes	Published Area Sunt. of Prod.				