Attachment C-103, Gulf Oil Corporation, G. C. Matthews well no. 12, Section 6, 20-5, 37-K, Lea County, New Mexico.

fellowing interval. 5661 to 5662; 5665-66; 5669-70; 5673-74; and 5677-78; and h holes each on a flat plane at 5584; 5573; 5568; and 5559;. Ran tubing and Baker FB packer. Set packer at 5650;. Acidised 7° casing perforations and Baker FB packer. Set packer at 5650; MCA. MP 2900%, min 1400%. OP 0%. IR 5662 to 5685; with 5000gallons of 15% NCA. MP 2900%, min 1400%. OP 0%. IR 3 bpm. Flushed with 23 BO. Pulled tubing and Baker FB packer. Ran 293/8° tubing, Baker FB packer and BP. Set BP at 5600; packer at 5536;. Swabbed tubing, Baker FB packer and BP. Set BP at 5600; packer at 5536;. Swabbed tubing, acidised 7° casing perforations 5559 to 5584; with 1000 gallons of 15% NEA. TP 5500%- 2500%. IR 3 bpm. Swabbed 104 BW, 0 oil in 12 hours. Pulled 2-/3/8° tubing. To be carried as temporarily abandoned.

THE COMMISSION SHIPLES TO SO