

DUPLICATE

FORM C-105

CR. 115 200 22700

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

0	•

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

THE TEXAS COMPANY

Drawer K, Wink, Texas

Company or Operator

Address

J. R. Phillips

Well No. 2

in NW $\frac{1}{4}$

of Sec. 6

T. 20-S

Lease

R. 37-E

N. M. P. M., Monument

Field,

Lea

County.

Well is 330 feet south of the North line and 330 feet west of the East line of NW $\frac{1}{4}$  of Sec 6

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is J.R.Phillips and Wife

Address Monument, N. M.

If Government land the permittee is

Address

The Lessee is THE TEXAS COMPANY

Address Box 2352 Houston, Texas

Drilling commenced April 2nd,

19 36

Drilling was completed May 9th,

19 36

Name of drilling contractor Oil Well Dlr. Company

Address Dallas, Texas

Elevation above sea level at top of casing 3570 (Ground)

The information given is to be kept confidential until

19

OIL SANDS OR ZONES

GAS ZONES

No. 1, from 3824	to 3890	No. 4, from 3050	to 3100
No. 2, from	to	No. 5, from 3140	to 3220
No. 3, from	to	No. 6, from 3270	to 3320

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
15 $\frac{1}{2}$ "	70	8	Lapweld	232'	Texas	Pattern			
9-5/8"	40	8	API	1049'	Halliburton				
7"OD	24	10	Api	3782'	Halliburton				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	15 $\frac{1}{2}$ "	252'	250	Halliburton		
	9-5/8"	1069'	700	"		
	7"OD	3800'	350	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 3890 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing on test May 12th, 19 36

The production of the first 24 hours was 164 bbls per hr with gas oil ratio of 1207 % was oil; %

emulsion; % water; and % sediment. Gravity, Be. 33.3

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Roy Rodgers

Driller

J. Foust

Driller

Russ Williams

Driller

S. A. Scott

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records

Subscribed and sworn to before me this 14th

Wink, Texas,

May 14, 1936

Place

Date

day of May, 1936

Name

Position

District Supt.

Representing

THE TEXAS COMPANY

Company or Operator

My Commission expires 5-31-37

Address Drawer K, Wink, Texas

DUPLICATE

## FORMATION RECORD

10/10/1957

FROM	TO	THICKNESS IN FEET	FORMATION
0'	150'	150'	Surface soil and caliche
150	265	115	Red rock and shells
265	372	107	Red beds and sand rock
372	770	398	Red beds and red rock
770	944	174	Red beds and lime shells
944	1008	64	Red rock and Anhydrite
1008	1102	94	Anhydrite
1102	2338	1236	Anhydrite and salt
2338	2445	107	Hard white anhydrite
2445	2491	46	Gyp and Anhydrite
2491	2620	129	Anhydrite and broken lime
2620	3042	422	Brown lime
3042	3680	638	Hard gray lime
3680	3781	101	Broken gray lime
3781	3885	104	Gray lime
3885	3890	5	Porous lime
			<b>TOTAL DEPTH 3890'</b>