

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-05957
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	41562
7. Lease Name or Unit Agreement Name	J.R. Phillips
8. Well No.	4
9. Pool name or Wildcat	Eumont Yates Seven Rivers Queen
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	3577' DF

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator Texaco Exploration and Production Inc.
3. Address of Operator P.O. Box 730 Hobbs, New Mexico 88240	4. Well Location Unit Letter F : 1980 Feet From The North Line and 1980 Feet From The West Line Section 6 Township 20-S Range 37-E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1) MIRUPU. Install BOP. TIH w/ 6 1/4" bit and 2 7/8" workstring to PBTD of 3308'. TOH. Rig up Atlas Wireline.

2) Run GR-CCL from PBTD to 2300'. Correlate to Lane log (3-9-51)

3) Using 4" casing gun perforate the following intervals with 15/32" bullets at 2 SPF: 3172,74,76,79,85,88,95,3200,04,09,13,20,23, 27,29,32,33,39,41,45,47,55,57,59,60,74,75,76,78,85,88,91,98,3300,02,04, (36 int; 72 holes)

(CONTINUED ON BACK)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE M.C. Duncan TITLE Engineer's Assistant DATE 3-13-92  
TYPE OR PRINT NAME M.C. Duncan TELEPHONE NO. 393-7191

(This space for State Use) SIGNED BY JERRY SEXTON

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAR 17 '92

CONDITIONS OF APPROVAL, IF ANY:

- 4) TIH w/ 7" treating pkr. and set @ +/- 3075'. Acidize Eumont  
perfs w/ 3500 g 15% NEFE acid and 100 balls. Drop 25 balls in the  
first 300 g of acid and space remaining balls evenly throughout the  
rest of the job. Pump @ as high a rate as possible without exceeding  
2300 psi.
- 5) Swab back acid.
- 6) Install production equipment. Place on test.

RECEIVED

MAR 16 1992

BOB HOBBS OFFICE