

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

MAY 17 1948

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within 30 days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF <del>SHOOTING</del> OR CHEMICAL TREATMENT OF WELL	<b>X</b>	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

May 13, 1948

Midland, Texas

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

**The Texas Company's** **J. R. Phillips** Well No. **5** in the  
Company or Operator Lease

**NW 1/4 NW 1/4** of Sec. **6**, T. **20-S**, R. **37-E**, N. M. P. M.,  
**Monument** Field, **Lea** County.

The dates of this work were as follows: **See below**

Notice of intention to do the work was (~~mailed~~) submitted on Form C-102 or **May 5** 19 **48**  
and approval of the proposed plan was (~~mailed~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

P B Depth: **5290 - Lime**

**5-1/2" casing cemented at 5770' with 750 sacks.**  
**Perforated 5-1/2" casing 5195-5220'. Perforated 5-1/2" casing 5170-5185'.**  
**Perforated 5-1/2" casing 5130-5160'.**

**With perforations 5195-5220' sealed off with Gel Seal and flakes and**  
**Dowell Pilot set at 5182', acidized perforated zone 5170-5185' with 1000**  
**(See over)**

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

**13th** day of **May**, 19 **48**Name **W. Blum**Position **Dist. Supt.**

Representing **The Texas Company**  
Company or Operator

My commission expires **June 1, 1949**Address **Box 1270, Midland, Texas**

Remarks:

FILED  
MAY 17 1948

**Ray Yarbrough**  
Name  
Title

J. R. Phillips (Cont'd)

Well no. 5

Gallons (Dowell) 15% acid. Completed 5-5-48. Swabbed 24 hours, 132 barrels fluid, 4% BSW.

Perforated 5-1/2" casing 5130-5160' with 150--1/2" holes. With packer set at 5189', acidized perforations with 500 gallons mud acid (Dowell) 5-7-48. Swabbed 15 hours test 160 barrels fluid, 3% BSW.

Tubing and packer were pulled. 2" tubing was run with 3' perforations at 5187'. Acidized with 6000 gallons 15% (western) acid, 5-8-48, perforations 5130-5160', 5170-5185' by using pumps on casing and tubing. Swabbed 45.52 barrels fluid in 24 hours, 20 - 48% acid water. Preparing to put well on pump.