



AREA 640 ACRES
LOCATE WELL CORRECTLY

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Anderson-Prichard Production Corporation, Hobbs, New Mexico
Company or Operator Address
H.M. Britt A Well No. 1 in C SE SW of Sec. 6 T. 20S
Lease
R. 37E N. M. P. M., Monument Field, Lea County.
Well is 4620 feet south of the North line and 3300 feet west of the East line of Sec 6-20S-37E
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is H.M. Britt Address
The Lessee is Address
Drilling commenced March 6 1936 Drilling was completed April 26 1936
Name of drilling contractor Olson Drilling Co. Address Tulsa, Oklahoma
Elevation above sea level at top of casing 3566 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3820 to 3906 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

| SIZE | WEIGHT PER FOOT | THREADS PER INCH | MAKE | AMOUNT | KIND OF SHOE | CUT & FILLED FROM | PERFORATED FROM TO | PURPOSE |
|--------|-----------------|------------------|------|--------|--------------|-------------------|--------------------|---------|
| 13" | 50# | 8 | SHLW | 269 | none | | | |
| 9-5/8" | 40# | 8 | Smls | 2397 | Baker | | | |
| 7" | 24# | 10 | Smls | 3812 | Halliburton | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

MUDDING AND CEMENTING RECORD

| SIZE OF HOLE | SIZE OF CASING | WHERE SET | NO. SACKS OF CEMENT | METHOD USED | MUD GRAVITY | AMOUNT OF MUD USED |
|--------------|----------------|-----------|---------------------|-------------|-------------|--------------------|
| 17" | 13" | 269 | 200 | Halliburton | | |
| 12" | 9-5/8" | 2397 | 750 | " | | |
| 8 1/2" | 7" | 3812 | 260 | " | | |

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

| SIZE | SHELL USED | EXPLOSIVE OR CHEMICAL USED | QUANTITY | DATE | DEPTH SHOT OR TREATED | DEPTH CLEANED OUT |
|------|------------|----------------------------|----------|------|-----------------------|-------------------|
| | | Jows 11 X | 1000 gal | 5-36 | 3812-3906 | |
| | | | | | | |
| | | | | | | |

Results of shooting or chemical treatment Gas Increased from 3-million CFRD to 13 million CFRD Cell Increased from 10 BOPN to 70 BOPN

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3906 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 19
The production of the first 24 hours was 720 barrels of fluid of which 94 % was oil; 0 % emulsion; 6 % water; and 0 % sediment. Gravity, Be. 32
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Herman Schweer Driller E.A. Hailes Driller
John Kiekhart Driller J.T. Latham Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

day of 19

Notary Public

My Commission expires

Hobbs, N.M. 6-10-37
Place Date
Name Jack H. May
Position Sec'y
Representing Anderson-Prichard Oil Corp.
Company or Operator

FORMATION RECORD

| FROM | TO | THICKNESS IN FEET | FORMATION |
|------|------|----------------------|---------------------------------------|
| 0 | 242 | 242 | Caliche and sand |
| 242 | 269 | 27 | Shells and redbeds |
| 269 | 436 | 167 | Sand and redbeds |
| 436 | 730 | 294 | Redbeds and shells |
| 730 | 830 | 100 | Redbeds and redrocks |
| 830 | 923 | 93 | Redrocks, and sandy lime shells |
| 923 | 1000 | 77 | Shale and shells |
| 1000 | 1230 | 230 | Shells and anhydrite |
| 1230 | 1295 | 65 | Shale, shells and salt |
| 1295 | 1330 | 35 | Anhydrite |
| 1330 | 1468 | 138 | Shale, shells, salt and anhydrite |
| 1468 | 1632 | 164 | Salt, shale and potash shells |
| 1632 | 1780 | 148 | Salt, anhydrite and potash |
| 1780 | 1945 | 165 | Salt, anhydrite, potash and salt |
| 1945 | 2070 | 125 | Salt, shale and potash |
| 2070 | 2090 | 20 | Anhydrite |
| 2090 | 2245 | 155 | Salt, shale and potash |
| 2245 | 2330 | 85 | Anhydrite |
| 2330 | 2445 | 115 | Anhydrite and lime |
| 2445 | 2625 | 180 | Lime |
| 2625 | 2675 | 50 | Lime and anhydrite |
| 2685 | 2945 | 270 | Lime |
| 2945 | 2984 | 39 | Lime and anhydrite |
| 2984 | 3035 | 51 | Lime |
| 3035 | 3089 | 54 | Shale, anhydrite and lime |
| 3089 | 3271 | 182 | Lime |
| 3271 | 3304 | 33 | Brown lime |
| 3304 | 3610 | 306 | Lime |
| 3610 | 3690 | 80 | Broken lime |
| 3690 | 3801 | 111 | Lime |
| 3801 | 3817 | 16 | Lime and broken lime, some saturation |
| 3817 | 3819 | 2 | Lime, showing of oil |
| 3819 | 3871 | 52 | Broken lime, saturated |
| 3871 | 3880 | 9 | Broken lime |
| 3880 | 3906 | 26 | Lime |
| 3906 | | | TOTAL DEPTH |