

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED
JAN 22 1951
OIL CONSERVATION COMMISSION
HOBBS OFFICE

WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

ANDERSON-PRICHARD OIL CORPORATION

1000 Apco Tower, Oklahoma City, Okla.

Company or Operator

Address

BRITT "A"

Well No.

3

in NE 1/4 SW 1/4

of Sec.

6

T.

20S

Lease

R. 37E N. M. P. M. Monument-Blinsbry Field, Lea County.

Well is 3150 feet south of the North line and 3150 feet west of the East line of Section 6

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is Las Cruces 031621-A Address

The Lessee is Address

Drilling commenced November 10th 1950 Drilling was completed December 30th 1950

Name of drilling contractor E. F. Moran Inc. Address Hobbs, New Mexico

Elevation above sea level at top of casing 3575 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 5164 to 5230 No. 4, from to

No. 2, from 5665 to 5730 No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
13-3/8"	34#	8 1/2 p. Jt.	SW	283'	None				Surface
8-5/8"	36#	8	Sals.	2686'	Baker		2 - 1" holes at 1770' to circulate cement above salt		Intermediate
	32#		Sals.						
	24.69#		LN						
5-1/2"	11# & 15.5#	8	Sals.	5720'	Baker		5669	5724	Producing string

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2"	13-3/8"	294	300	HOMO		Water
11"	8-5/8"	2669	2000	"		Salt water
7-3/4"	5-1/2"	5729	750	"	8.8	Hole full

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Type J 15% HCL	500 gals.	1-6-51	5669-5724	-

Results of shooting or chemical treatment Cleaned perforations

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 5730 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing January 14th 1951

The production of the first 24 hours was 110.7 barrels of fluid of which 98 % was oil;

emulsion; % water; and 2 % sediment. Gravity, Be. 38.8

If gas well, cu. ft. per 24 hours - Gallons gasoline per 1,000 cu. ft. of gas -

Rock pressure, lbs. per sq. in. -

EMPLOYEES

R. W. Reynolds Driller D. R. Smith Driller

A. E. Rutledge Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 16th

Hobbs, New Mexico 1-16-51

day of January 19 31

Name C. M. Carlow

Position Production Foreman

Represented Anderson-Prichard Oil Corporation

Address Box 1697, Hobbs, N.M.

My Commission expires April 23, 1952

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	42	42	Sand, Caliche
42	78	36	Caliche, Gravel
78	786	708	Red Bed
708	1460	752	Red Bed, Anhydrite
1460	2335	875	Anhydrite, Salt
2335	2992	657	Anhydrite, Lime
2992	3120	128	Lime
3120	3381	261	Anhydrite, Lime
3381	3529	148	Lime
3529	3581	52	Lime, Anhydrite
3581	5147	1566	Lime
5147	5200	53	Lime, Sand
5200	5638	438	Lime
5638	5673	35	Dolomite, Lime
5673	5730	57	Lime