

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M.L. Oil Conservation Division
811 B.O. 3011880
Artesian No. 88242834
FORM APPROVED
Bureau No. 1004-0135
Expires: March 31, 1993
Lease Designation and Serial No.
NMLC031621A

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT - " for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☐ Oil Well ☐ Gas Well ☒ Other	6. If Indian, Allottee or Tribe Name
2. Name of Operator Amerada Hess Corporation	7. If Unit or CA, Agreement Designation
3. Address and Telephone No. P. O. Drawer D, Monument, N.M. 88265 505 393-2144	8. Well Name and No. Britt "A" 4
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 990' FSL & 2280' FWL, Sec. 6, T20S, R37E	9. API Well No. 30-025-0596900
	10. Field and Pool, or exploratory Area Monument Paddock
	11. County or Parish, State Lea County N.M.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	
☒ Notice of Intent	☒ Abandonment	☐ Change of Plans
☐ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment Notice	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut-Off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Please refer attached plugging procedure.

RECEIVED
NOV 14 10 56 PM '96
BUREAU OF LAND MANAGEMENT

14. I hereby certify that the foregoing is true and correct
Signed [Signature] Title Senior Production Foreman Date 11-14-96

(This space for Federal or State office use)

Approved (ORIG. SGD.) ALEXIS C. SWOBODA Title PETROLEUM ENGINEER Date 11/25/96

Conditions of approval, if any:

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

BRITT 'A' #4
PROCEDURE TO PLUG AND ABANDON

1. NOTIFY BLM 24 HOURS PRIOR TO RIG UP.
2. MIRU PU.
3. INSTALL BCP.
4. TIH W/GAGE RING & TBG.
5. TAG CIBP @ 5100'
6. CIRCULATE HOLE W/PLUG MUD.
7. RU PUMP TRUCK.
8. ESTABLISH PUMP RATE AND SPOT ³⁵/₂₅ SK PLUG ON TOP OF CIBP.
9. DISPLACE W/PLUG MUD.
10. TOH W/1800' OF TBG AND LAY DOWN.
11. SPOT CEMENT BALANCE PLUG W/25 SKS OF CLASS 'C' CMT @ 3420'.
12. DISPLACE W/PLUG MUD.
13. TOH W/TBG.
14. RU WIRELINE.
15. PERF @ 1120' W/ 2 SHOTS.
16. RD WIRELINE.
17. TIH W/TBG AND PACKER.
18. ESTABLISH INJ RATE W/PACKER INTO PERFS @ 1120'.
19. IF PUMP RATE CAN NOT BE ESTABLISHED ACIDIZE PERFS.
20. TOH W/TBG AND PACKER.
21. TIH W/TBG AND CMT RETAINER.
22. SET RETAINER @ 970'.
23. SQZ AND CIRC. PERFS. @ 1120' W/35 SXS CMT.
24. DISPLACE W/PLUG MUD.
25. TAG CMT PLUG.

26. TOH W/TBG.
27. RU WIRELINE.
28. PERF @ 694' W/ 2 SHOTS.
29. RD WIRELINE.
30. TIH W/TBG AND PACKER.
31. ESTABLISH INJ RATE W/PACKER INTO PERFS @ 694'.
32. TOH W/TBG AND PACKER.
33. IF PUMP RATE CAN NOT BE ESTABLISHED ACIDIZE PERFS.
34. TIH W/TBG AND CMT RETAINER.
35. SET RETAINER @ 544'.
36. SQZ AND CIRC. PERFS. @ 1120' W/35 SXS CMT.
37. DISPLACE W/PLUG MUD.
38. SPOT 11 SX CLASS C CMT @ 100' IN 5 1/2" CSG.
39. CUT OFF WELLHEAD.
40. WELD ON PLATE AND DEADMAN MARKER.
41. CLEAN SITE.

BKHII A No. 4
 API 3002505969
 NUMBER OF COMPLETION(S) 2



5142.0 5154.0' PERIS
 5190.0 5210.0' PERIS
 5585.0 5612.0' PERIS
 5660.0 5724.0' PERIS

TOWNSHIP 020S RANGE 031
 00990 FSL 02280 FWL SEC 0006

KB ELEV: 3578'
 ID: 5727'

5100.0 5102.0' CIBIP
 5270.0 5272.0' CIBIP
 5640.0 5642.0' RETAINER
 5726.0 5728.0' OD PROD CSC
 5628.0 5640.0' CEMENT PLUG
 5642.0 5725.0' CEMENT PLUG
 5725.0 5728.0' CEMENT PLUG

00990 FSL 02280 FWL SEC 0006