

(Revised 7/1/52)
(Form C-106)

RECEIVED
NATION COMMISSION
Mexico
OCT 23 1953
OIL CONSERVATION COMMISSION
CORD
HOBB5-OFFICE

Result of Production Stimulation After 2000 Gal. Treatment, Swabbed 92 Bbl Load Oil & 34 Bbl Acid Water
in 13 Hours. After 4000 Gal Treatment, Flowed & Swabbed 127 Bbl Load Oil & 65 Bbl New Oil
in 34 Hours. Depth Cleaned Out 5680'

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from Surface feet to 5700 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 8-11-53, 19 53

OIL WELL: The production during the first 24 hours was 204 barrels of liquid of which 100 % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 39

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy.	T. Devonian	T. Ojo Alamo
T. Salt	T. Silurian	T. Kirtland-Fruitland
B. Salt	T. Montoya	T. Farmington
T. Yates	T. Simpson	T. Pictured Cliffs
T. 7 Rivers	T. McKee	T. Menefee
T. Queen	T. Ellenburger	T. Point Lookout
T. Grayburg	T. Gr. Wash	T. Mancos
T. San Andres	T. Granite	T. Dakota
T. Glorieta 5050'	T. Paddock 5155'	T. Morrison
T. Drinkard	T. Elinebry 5618'	T. Penn.
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	248	248	Sand & Caliche				
248	749	501	Redbed				
749	900	151	Redbed & Anhydrite				
900	1048	148	Redbed & Redrock				
1048	1120	72	Anhydrite				
1120	2314	1194	Anhydrite & Salt.				
2314	2356	42	Anhydrite				
2356	2398	42	Anhydrite & Lime				
2398	2463	65	Anhydrite & Gyp				
2463	2494	31	Lime				
2494	2522	28	Anhydrite & Lime				
2522	2590	68	Lime & Shale				
2590	2645	55	Lime & Anhydrite				
2645	3042	397	Lime				
3042	3367	325	Lime & Sand				
3367	3538	171	Lime				
3538	3622	84	Lime, Sand, & Shale				
3622	5700	2078	TD Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

October 23, 1953

(Date)

Company or Operator Sinclair Oil & Gas Company

Address Box 1927, Hobbs, New Mexico

Name

Position or Title Dist. Supt.