

Orig: & cc: OGC
cc: FMR
JTR
FNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 22, 1955

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company

(Company or Operator)

Bertha J. Barber

(Lease)

Gaskle Drilling Company

(Contractor)

Well No. 17 in the NE 1/4 SE 1/4 of Sec. 7

T. 20 S, R. 37 E, NMPM, Monument-Blinnery Pool, Lea County.

The Dates of this work were as follows: 4-17-55

Notice of intention to do the work (yes) (was not) submitted on Form C-102 on _____, 19____.

(Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 5674 - set 7" OD casing @ 5673 and cemented with 350 sacks cement. Ran temperature survey which indicated top of cement back of 7" casing @ 2700 feet from surface. Let cement set 72 hours and drilled plug to 5670, tested casing w/1,000# pump pressure for 30 minutes before and after drilling plug. No decrease in pressure.

Ran Lane Wells Gamma Ray & Neutron logs, perforated 7" casing w/4 jet shots per foot from 5624-33, 5636-40, 5644-53, 5656-61, 5666-70. Ran 6/ 5665 feet of 2" UE tubing. Stabbed well clean of load water, flowed to tanks 284 barrels of clean oil in 9 hours, thru 1/2" choke with tubing pressure of 190#, casing pressure 325#.

Witnessed by H. A. Lund Sinclair Oil & Gas Co. Foreman
(Name) (Company) (Title)

Approved J. G. Stanley
OIL CONSERVATION COMMISSION
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name C. E. KitterPosition Dist. Supt.Representing Sinclair Oil & Gas CompanyAddress 520 East Broadway, Hobbs, New Mexico