NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING	REPORT ON RESULT OF TEST	X	REPORT ON
DRILLING OPERATIONS	OF CASING SHUT-OFF		REPAIRING WELL
REPORT ON RESULT	REPORT ON RECOMPLETION		REPORT ON
OF PLUGGING WELL	OPERATION		(Other)

October 23, 1954	Hobbs, New Mexico
(Date)	(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sunray Oil Corporation	A•	Cooper	•	
(Company or Operator)	(Lease)			
Frank Frawley Drilling Company	., Well No. 10	in the	NW 1/4 of Sec. 7	
(Contractor) T. 20-S., R. 37-E., NMPM., Monument-Blinebry				
The Dates of this work were as follows:	1954			

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Set 13 358" Armco Spiral Weld Casing, 36#, at 577' with 650 sacks of Longhorn cement. Circulated cement to surface. Cemented with single plug method, stopping plug at 542'. Measurements by displacement from Halliburton truck tanks... Casing was tested to 1200 psi. for 30 minutes with no pressure drop. Test made with clear water using rig pumps.

Witnessed byT. Shaker	Frank Frawley Drilling Company	Tool Pusher
Approved: OLE CONSERVATION COMMISSION	to the best of my knowledge	poration