

WELL DATA SHEET

LEASE Britt WELL NO. 6 FIELD Eunice-Manurewa DATE 7-11-95

LOCATION 660' FEET FROM South LINE AND 1980' FEET FROM West LINE

SECTION 7 TOWNSHIP 20-S RANGE 37-E COUNTY Lea STATE N.M.

Lease Desig. + S.N. = NMLC031621A API Well # 30-025-059940081

* WH conn: 9 5/8" Flange - 6' below G.L.

Date Completed 7-10-95 P+A ops.

Initial Formation

FROM: TO:

Initial Production BOPD BWPD
MCFPD GOR

Completion Data:

1970-7 Set Cmt. Retainer @ 3727' + 592. O.H.
From 3856' to 3750' w/ 100 sx. Class "H" Cmt.
7-7-95 Set CIRC @ 3445' + 592. w/ 150 sx.
Class "C" Cmt. - Obtained 1200 psi Surface
Press. Running 592. w/ 100 sx Below CIRC.
Pump 50 sx. on top CIRC - TOC @ 3255'
Cut 7" Csg. off @ 2500' + Pull 7" Csg.
7-10-95 Spot P.A. Mud f/ 3255' up to 2600'.
Spot 200 sx Class "C" w/ 20% CaCl₂ Cmt. Plug
From 2631' up to 2045' (Tagged Plug) - Circ.
P.A. Mud f/ 2045' up to Surface. - Spot 68 sx
Class "C" Neat Cmt. f/ 1210' up to 1006' - Perf
9 5/8" Csg. @ 300' - Pump 225 sx. Class "C" Neat
Cmt. down 9 5/8" Csg. thru 592 holes @ 300'
+ Back up 9 5/8" x 13" Surface Csg. Ann.
Let 7" Csg. Full of Cmt. f/ Surface to 300'.
Subsequent Workover or Reconditioning:

Surf. GE: _____
KDB to GE: _____
DF to GE: _____

13" OD lbs.
Surf. Pipe set @
254' w/ 250 sx
cmt. Circ? Yes
TOC @ 1200' by Calc.

9 5/8" OD lbs.
- Thd Gr -
- Csg set at
2457' w/ 600 sx
Cmt. Circ? No
TOC at 1200' by
Calc

TOC @ 2600' by Calc.

AUG 8 1995

Present Prod. BOPD BWPD
MCFPD GOR
Date

Remarks or Additional Data:

P+A ops. Monitored by BLM Rep
Steve Coffey - Hobbs N.M.

PBD Surface

TD 3856'

J.B. Cantor

RECEIVED

AUG 3 6 1

UCD ADMIN
OFFICE