



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Anderson-Prichard Oil Corporation      Hobbs, New Mexico.  
Company or Operator      Address  
H.M. Britt      Well No. 6      in SE SW 7 of Sec. 7, T. 20S  
Lease  
R. 37E      N. M. P. M., Monument      Field, Lea      County.  
Well is 4620 feet south of the North line and 3300 feet west of the East line of Sec 7-20S-37E  
If State land the oil and gas lease is No.      Assignment No.        
If patented land the owner is      Address        
If Government land the permittee is H.M. Britt      Address        
The Lessee is      Address        
Drilling commenced 11-22 1936      Drilling was completed 12-27 1936  
Name of drilling contractorHerschback Drilling Co., Address Dallas, Texas  
Elevation above sea level at top of casing 3547 feet.  
The information given is to be kept confidential until 19     

OIL SANDS OR ZONES

No. 1, from 3800 to 3856      No. 4, from      to        
No. 2, from      to      No. 5, from      to        
No. 3, from      to      No. 6, from      to     

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.  
No. 1, from      to      feet.        
No. 2, from      to      feet.        
No. 3, from      to      feet.        
No. 4, from      to      feet.     

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"	40#	8	LW	254	none			
9-5/8"	40#	8	Smls	2457	HOWCCo			
7"	24#	8	"	3750	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17"	13"	254	250	HOWCCo	11# gal	circulated
12"	9-5/8"	2457	600	"	"	"
8 1/2"	7"	3750	280	"	"	"

PLUGS AND ADAPTERS

Heaving plug—Material      Length      Depth Set        
Adapters—Material      Size     

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment        
     

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3856 feet, and from      feet to      feet  
Cable tools were used from      feet to      feet, and from      feet to      feet

PRODUCTION

Put to producing 12-28 1936  
The production of the first 24 hours was 495 barrels of fluid of which 100 % was oil; 0 % emulsion; 0 % water; and 0 % sediment. Gravity, Be 32.0  
If gas well, cu. ft. per 24 hours      Gallons gasoline per 1,000 cu. ft. of gas        
Rock pressure, lbs. per sq. in.     

EMPLOYEES

W.L. Payne      Driller      Deck Schoeb      Driller  
B.T. O'Neal      Driller      B.E. Jackson      Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this      Place      Date        
day of      19      Name      Frank Gray

## FORMATION RECORD.

FROM	TO	THICKNESS IN FEET	FORMATION
0	230	230	Caliche, sand and shells
230	290	60	Broken sand rock
290	675	385	Bedgeds
675	854	179	Redbeds and redrock
854	934	80	Redbeds and shells
934	998	64	Redrock and shells
998	1250	252	Redrock and anhydrite
1250	1295	45	Potash and shells
1295	1310	15	Anhydrite
1310	1385	75	Potash and shells
1385	1440	55	Redrock and anhydrite
1440	1490	50	Anhydrite shells
1490	1605	115	Salt shells
1605	1860	255	Salt
1860	2020	160	Salt streaks of anhydrite
2020	2110	90	Salt and shells
2110	2135	25	Anhydrite
2135	2170	35	Salt and shells
2170	2260	90	Salt
2260	2298	38	Salt and shells
2298	2355	57	Anhydrite and broken anhydrite
2355	2400	45	Anhydrite and lime shells
2400	2465	65	Anhydrite
2465	2514	49	Anhydrite and lime
2514	2550	36	Anhydrite
2550	3123	573	Lime
3123	3130	7	Lime - show of oil
3130	3557	427	Lime
3557	3588	31	Anhydrite and lime
3588	3856	268	Lime