W.M. OIL CONS. COMMISSION HORBS NEW MEXICO 88240 P.Q. BOX 1980 FORM APPROVED UNITED STATES Form 3160-5 Budget Bureau No. 1004-0135 (June 1990) DEPARTMENT OF THE INTERIOR Expires: March 31, 1993 **BUREAU OF LAND MANAGEMENT** ease Designation and Serial No. MMLC031621A SUNDRY NOTICES AND REPORTS ON WELLS 6/ If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoirs Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Gas Well 8. Well Name and No. 2. Name of Operator Britt No. 7 MKA Oil Properties 30-025-0599500SI 3. Address and Telephone No. 10. Field and Pool, or Exploratory Area 500 W. Texas, Suite 1230, Midland, TX 79701 Eunice Monument 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) (915) 684-8442 11. County or Parish, State 1650' FSL & 1650' FEL, Sec. 7, T20S - 37E Lea County, NM Lea County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Change of Plans New Construction Recompletion Subsequent Report Plugging Back Non-Routine Fracturing Water Shut-Off Casing Repair Final Abandonment Notice Conversion to Injection Dispose Water Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 7/18/95 Set CICR at 3400' and squeezed OH 3804 - 3879' to 1200 psig w/ 140 sx. cement below CICR. Dumped 10 sx. on top od CICR. 7/19/95 Cut 7" csg. at 2500' & POH w/ 7" csg. RIH w/ tbg. to 3300'. Spotted mud fr. 3300' to 300'. Spotted 175 sx 7/20/95 cement fr. 2600' to 2079'. WOC 1-1/2 hrs. Tagged cement at 2100'. Perf. 9-5/8" csg. w/ 4 squeeze holes at 300'. Spotted a 35 sx. plug fr. 1223' to 1115'. POH w/ tbq. Pumped 190 sx. cement down 9-5/8" thru squeezed holes at 300' & up 9-5/8" x 13" annulus. cement to pits leaving 9-5/8" & 13" csq. full of cement. 7/21/95 Installed dry hole marker, backfilled cellar, dug up anchors. & leveled location. P&A operations monitored & approved by Steve Caffey. Approved as to bugging of the web pore Liability under bond is retained until surface restoration is completed. that the foregoing is prue an onnie H. Westrock Vice-President Title (This space for recent or State office user