

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	<input checked="" type="checkbox"/>
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

December 27, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation T. Anderson Well No. 2 in the _____
Company or Operator Lease
SE¹ of the SE¹ of Sec. 8, T. 20, R. 37, N. M. P. M.,
Monument Field, Lea County.

The dates of this work were as follows: December 21, 1949

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on December 21, 1949
and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

3850' - Total Depth, 3830' Plug Back Depth, 6-5/8" Casing set at 3784'
Rigged up Mobil Unit and pulled 2-7/8" Tubing. Ran Sand Pump and cleaned hole out to T.D.
Ran Lane-Wells Gamma Ray and Neutron Survey. Lane-Well checked bottom at 3851'
Dumped at intervals a total of 4 sacks of Incon Cement using a Dump Bailer. Measured up
and found top of plug at 3830'. Ran backs in hole with 2-7/8" Tubing and Packer. Set
Packer at 3740' and Tubing at 3822'. Rigged up and pulled Swab one time and well started
flowing. In 15 hours well flowed 221.47 bbls. of pipe line oil. No Water. GOR 315
Well placed back on production

Witnessed by D.F. Furse Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this _____
4 day of Jan. 1950

I hereby swear or affirm that the information given above
is true and correct.

Name Dr. Topp

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires 10/24/53

Address Drawer "D" Monument, New Mexico

Remarks:

APPROVED

305

Roy Yankovich
Name
Title