

NEW MEXICO OIL CONSERVATION COMMISSION

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back and Perforating 7" Casing	<input checked="" type="checkbox"/>

January 16, 1952

Date

Hobbs, New Mexico

Place

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation B. Whitwire Well No. 2 in the
Company or Operator Lease
 NW NE of Sec. 8, T. 20S, R. 37E, N. M. P. M.,
 Monument Pool Lea County.

The dates of this work were as follows: Completed January 5, 1952

Notice of intention to do the work was (was not) submitted on Form C-102 on January 7, 1952, and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On January 2, 1952, ran Lane Wells surveys, ran 7" Model "K" cement retainer with 1/2 sack cement on wire line set at 3880'. Tested retainer and cement with 300# pressure for 30 minutes. There was no drop in pressure. Ran SLM found top of cement at 3797'. On January 5, 1952, perforated 7" casing from 3760' to 3790' w/4 jet holes per foot by Lane Wells. On January 6, acidized w/1000 gallons 15% NE acid by C. P. TP 1500-700#. CP 1500-1000#. Average injection rate 42 GPM. Injection time 24 min. Duration 1 hour and 5 minutes.

Production before: 5 bbls per day. Penalized because of high GOR. GOR 32,534.

Production after: Flowed 64-1/2 bbls oil in 6 hours. GOR 1813.

Witnessed by N. B. Jordan Gulf Oil Corporation Field Foreman
Name Company Title

APPROVED:
 OIL CONSERVATION COMMISSION

Roy Yarkbrough
Name Title
 Date, 19

I hereby swear or affirm that the information given above is true and correct.

Name E. H. Taylor
 Position Area Prod. Supt.
 Representing Gulf Oil Corporation
Company or Operator
 Address Box 2167, Hobbs, N. M.