

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.
10-031736(3)
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SEC., T., R., M., OR S.W. AND
SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

LEA NM

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

PAN AMERICAN PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

BOX 68, HOESS, N. M. 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL x 660' FWL Sec 8/10.7N, 50W, S44

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

RDB 3353

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☒

ALTERING CASING ☐

ABANDONMENT* ☐

(Other) ☐

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

In an effort to restore well to production status
remedial work performed as follows:

Set cement retainer @ 3760' and squeezed open hole
section 3763-3830 w/170 Lb. neat oil 1/2" TDF Plug /SNR. Max 2500 PSI.

(TCMT-PAD. 3760') FERT INTERVALS 4251, 3716, 26, 32, 36, 40, 451.

Graded w/250 gal 15%. Conducted.

PROD - PMP 0 80 x 128 BW 24 hours

AFTER - FLW 70 20 x 0 BW 3 hrs. GOR 1500, 1 1/2" CB. TPF-250.

TD-3860'.
PAD-3760'

OC-1-5-68

COMP-1-15-68

2 1/2" TDF 3766

7" C/A 3763'

18. I hereby certify that the foregoing is true and correct

SIGNED

AREA SUPERINTENDENT

TITLE

DATE

1-19-68

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

APPROVED

JAN 23 1968

J L GORDON
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

044- USGS-12
1- NSW
1- DSDP
1- RRY