
NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico



MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is compl rc in

	of the Commission. Indicate Nature of Report by Cl	ecking Bel	ow	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TO CASING SHUT-OFF	EST X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETY OPERATION	ON	REPORT ON (Other)	
	June 15, 1	53	Hobbs, New 1	exico
	done and the results obtained under to			
Sinclair 011 & Gas Comp	any orator)	В. Ј	(Lease)	***************************************
Milhoan Drilling Compan	y , Well N	.10	in the 1/4	¹ / ₄ of Sec,
(Contractor	Monument	Pool,	Lea	County.
r, R, INVII WI.,				
The Dates of this work were as follows:	6-8-53			•
- de de mark (hibs	(was not) submitted on Form C-102	on	incorport words)	, 19
			(Cross out meditect words)	
and approval of the proposed plan (was	s) (was not) obtained.			
DETA	ILED ACCOUNT OF WORK DONE	AND RESU	ULTS OBTAINED	
	ILED ACCOUNT OF WORK DONE	AND RESU	JLTS OBTAINED	
Spudded 6-5-53				- Administration
Spudded 6-5-53				- eirculated
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	easing @ 999 and comented	with 10	00 sacks of cement	
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	casing @ 999 and comented	edth 10	00 sacks of cement	ment plug and
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	casing @ 999 and comented	edth 10	00 sacks of cement	ment plug and
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	easing @ 999 and comented	edth 10	00 sacks of cement	ment plug and
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	casing @ 999 and comented	edth 10	00 sacks of cement	ment plug and
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	casing @ 999 and comented	edth 10	00 sacks of cement	ment plug and
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	casing @ 999 and comented	edth 10	00 sacks of cement	ment plug and
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface.	casing @ 999 and comented	edth 10	00 sacks of cement	ment plug and
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface. Let cement set for 48 ho retested with 1000# for	casing @ 999 and cemented ours and tested with 1000# 30 minutes. No decrease	with 10 pump pr in press	00 sacks of cement ressure, drilled centure, resumed drilli	ment plug and ing.
Spudded 6-5-53 TD - 1000 - Set 13 3/8" surface. Let cement set for 48 ho retested with 1000# for Witnessed by Joseph J.	casing @ 999 and comented ours and tested with 1000# 30 minutes. No decrease	pump prin press	00 sacks of cement ressure, drilled centure, resumed drilli	ment plug and ing.
Spudded 6-5-53 TD - 1000 - Set 13 3/8" (surface. Let cement set for 48 ho retested with 1000# for	oasing @ 999 and comented ours and tested with 1000# 30 minutes. No decrease . Wright Sinelain	pump prin press	cessure, drilled convert resumed drilled convert resum	ment plug and ing.
Spudded 6-5-53 TD - 1000 - Set 13 3/8" surface. Let cement set for 48 ho retested with 1000# for Witnessed by	casing @ 999 and comented ours and tested with 1000# 30 minutes. No decrease Wright Sinelain	pump prin press	Cas Co. Assistant	ment plug and ing.
Spudded 6-5-53 TD - 1000 - Set 13 3/8* surface. Let cement set for 48 ho retested with 1000# fer Witnessed by	ours and tested with 1000% 30 minutes. No decrease Wright Sinelain (Comp.) I he to te	pump prin press	cessure, drilled converted that the information given about that the information given about that the information given about the converted to	ment plug and ing.
Spudded 6-5-53 TD - 1000 - Set 13 3/8" surface. Let cement set for 48 ho retested with 1000# for Witnessed by	oasing @ 999 and comented ours and tested with 1000# 30 minutes. No decrease Wright Sinelain (Comp	pump prin press	Cas Co. Assistant	ment plug and ing.
Spudded 6-5-53 TD - 1000 - Set 13 3/8" surface. Let cement set for 48 ho retested with 1000# for Witnessed by	ours and tested with 1000% 30 minutes. No decrease Wright Sinelain (Comp. I he to	pump prin press	Cas Co. Assistant that the information given above the supt.	ment plug and ing.