



NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

1954 MAY 13 AM 8:50

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other) <b>Kill well</b>	<input checked="" type="checkbox"/>

May 15, 1954

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company

(Company or Operator)

Bertha J. Barber

(Lease)

Milhean Drilling Company

(Contractor)

Well No. **13** in the **S** **NW** **8**  $\frac{1}{4}$  of Sec.

T. **20 S**, R. **37 E**, NMPM, **Monument** Pool, **Lea** County.

The Dates of this work were as follows: **3-12-54 to 4-15-54**

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 2900 - Set 9 5/8" casing @ 2894'. Was preparing to cement, well blew out, caught fire, burned down drilling rig.

Layed lateral lines from well. Extinguished fire. Moved in small rotary rig to kill well. Well caught fire and burned small rotary rig.

Extinguished flame. Installed control equipment. Moved in pulling machine, ran 2860' of 2 1/2" UE tubing, perforated 9 5/8" casing with 80, 3/8" holes 2760 to 2780. Pumped in 600 barrels of 10.3# salt water and 600 barrels of 14# mud, unable to kill well.

Ran 2850' of 5" casing, perforated 5" casing and 9 5/8" casing w/3 - 1/2" shots per foot from 2760 to 2780, pumped in 1800 barrels of 12# mud outside of 9 5/8" casing, pumped 1200 barrels of 12# mud down 5" casing and killed well.

Witnessed by **Homer E. McIntire, Jr.**  
(Name)

**Sinclair Oil & Gas Co.**  
(Company)

**Asst. foreman**  
(Title)

Approved: **OIL CONSERVATION COMMISSION**

*S. J. Stanley*  
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **B. B. Barber**

Position **Dist. Supt.**

Representing **Sinclair Oil & Gas Co.**

Address **Box 1927 Hobbs, New Mexico**

(Title)

(Date)