F

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

nstructions in the Rules and Regulations of th	Indicate Nature of Report by Checking	Below	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)	
	September 1, 195	Hobbs, New Mexico	
Following is a report on the work done	(223)	ing noted above at the	
Sinclair "il & Gas Company	_	tha J. Barber	
(Company or Operator)		(Lease) NW	.
		Lea	
(1)	not) submitted on Form C-102 on		19
Notice of intention to do the work to all twas			
		(Cross out incorrect words)	
		(Cross out incorrect words)	
and approval of the proposed plan (was) (was	not) obtained. ACCOUNT OF WORK DONE AND R	ESULTS OBTAINED	
DETAILED DETAILED TD 2900, set 9 5/8" OD casing ature survey which indicated Let cement set 48 hours and cement plug. Ne decrease in	ACCOUNT OF WORK DONE AND R © 2879 and semented with top of cement @ 1320 feet sested with 1200 psunds for pressure. Resumed drilling	esults obtained 1400 sacks of cement. Ran tem from surface. 1 hour before and after drilling	per- ing
DETAILED TD 2900, set 9 5/8" OD casing ature survey which indicated	anot) obtained. ACCOUNT OF WORK DONE AND R C 2879 and comented with top of coment @ 1320 feet costed with 1200 pounds for	esults obtained 1400 sacks of cement. Ran tem from surface. 1 hour before and after drilling	per- ing
DETAILED TD 2900, set 9 5/8" OD casing ature survey which indicated Let cement set 48 hours and cement plug. No decrease in	Sinclair Oil & G as (Company) I hereby cert to the best of Name	1400 sacks of cement. Can tem from surface. 1 hour before and after drill 18 Company Assistant forces (Title) Ty that the information given above is true and of my knowledge.	per- ing
TD 2900, set 9 5/8" OD casing ature survey which indicated Let cement set 48 hours and cement plug. No decrease in Witnessed by	Sinclair Oil & G as (Company) I hereby cert to the best of Name	1400 sacks of cement. Can tem from surface. 1 hour before and after drill 13 Company Assistant for em (Title)	per- ing

(Title)