

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on result of Chemical treatment And Packer Setting	

Hobbs, New Mexico Place **July 16, 1938.** Date

OIL CONSERVATION COMMISSION,
 Santa Fe, New Mexico.

Gentlemen:

DUPLICATE

Following is a report on the work done and the results obtained under the heading noted above at the _____
Tide Water Assoe Oil Company. T. Anderson Well No. **2** in the _____
 Company or Operator Lease
SEt of Sec. **8**, T. **20**, R. **37**, N. M. P. M.,
Monument Field, **Lea** County.

The dates of this work were as follows: **July 12 and 13th, 1938**
 Notice of intention to do the work was [was not] submitted on Form C-102 on **6/14/38** 19____
 and approval of the proposed plan was [~~was not~~] obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was completed November 10, 1936 for 44-bbls oil per hour w/gas oil ratio of 592 cu. ft per barrel of oil natural. 7"OD Casing set at 3804'. Top white lime 3830', total depth 3880'. At time of remedial work the gas oil ratio had increased to 12,541 cu ft per barrel. Killed well with water, using approx 400-bbls, and run Exner-Dodge 5-3/4"OD 32" rubber underset Packer set at 3847' and swabbed dry w/small show of gas, raised Packer to 3827' and swabbed 6 to 8 bbls oil per hour with small amount of gas. Treated with 500-gallons of Dowel X Acid and after clean of acid tested 21-bbls oil per hour with 180,000 cu ft gas. Gas Oil Ratio 357. After pinching well in to a 5/64" choke TP 100# it produced 45-bbls oil per day with 27,000 cu ft gas, gas oil ratio 600.

Witnessed by **Lloyd Lamb** **Tide Water Assoe Oil Company**
 Name Company

Subscribed and sworn to before me this **16**
 day of **July**, 19 **38**
Lance Sparks
 Notary Public

My Commission expires **November 22, 1941.**

I hereby swear or affirm that the information given above is true and correct.

Name **Elmer Purnell**
 Position **Prod. Sup't.**
 Representing **Tide Water Assoe Oil Company**
 Company or Operator
 Address **Drawer KK, Hobbs, New Mexico.**

Remarks:

Ross Walker R.M.
 Name
Oil & Gas Inspector
 Title

118511

118511