

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate  
(Other instructions  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

6. LEASE DESIGNATION AND SERIAL NO.

031736 A

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gilluly - Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Monument Paddock

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8, T-20-S, R-37-E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

1. OIL WELL  GAS WELL  OTHER

2. NAME OF OPERATOR  
Rodman Petroleum Corporation

3. ADDRESS OF OPERATOR  
Box 3826, Odessa, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

Unit M, 990' FSL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3555 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Casing Record: 10-3/4" csg set at 1026' - cement circulated.  
7-5/8" csg set at 3358' - cmtd w/ 400 sx - top cmt @ 1705', Top salt approx 2200'.  
5-1/2" csg set at 5108' - cmtd w/ 200 sx - 4% gel, top cmt at 4700'.

Proposal: Note: mud will be used between all cement plugs.  
(a) Spot 100' plug or 15 sx min plug across abnd prod. zone (open hole)  
(b) Cut & recover 5-1/2" csg (4000'), spot 100' plug across stub of 5-1/2" csg.  
(c) Spot 100' plug across shoe of 7-5/8" csg.  
(d) Cut & recover 7-5/8" csg (1500'), spot 100' plug across stub of 7-5/8" csg.  
(e) Spot 100' plug across shoe of 10-3/4" csg and 20 sx plug at top of 10-3/4" csg, fill cellar & place marker.  
(f) All offset operators have been notified.

Offset Operators:  
Sinclair Oil & Gas Co., Box 1920, Hobbs, New Mexico  
Amerada Petroleum Corporation, Box 668, Hobbs, New Mexico  
Gulf Oil Corporation, Box 670, Hobbs, New Mexico  
Phillips Petroleum Company, 4th & Washington, Odessa, Texas, Attn: Mr. W. C. Rodger  
R. E. Honeyman, Jr., Attn: Vic Short, Agent, Hobbs, New Mexico

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE

1-3-66

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

APPROVED  
JAN 26 1966  
A. H. BROWN  
DISTRICT ENGINEER