1. 11

NEW . XICO OIL CONSERVATION COM' SSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

OTICE OF INTENTION TO TEST CASING SHUT-OFF	x	NOTICE OF INC	TENTION TO S	SHOOT OR	
OTICE OF INTENTION TO CHANGE PLANS		NOTICE OF IN OTHERWISE	TENTION TO E ALTER CASI	PULL OR	
OTICE OF INTENTION TO REPAIR WELL		NOTICE OF IN	TENTION TO I	PLUG WELL	
OTICE OF INTENTION TO DEEPEN WELL					
Monument, New		ico Place	Je.	bruary 27	1937
IL CONSERVATION COMMISSION,					
anta Fe, New Mexico.					
entlemen:					
ollowing is a notice of intention to do certain work a	as desci	ribed below at the)		
merada Petroleum Corporation	Lgu	ighlin t	Well No	1 in NW	M d
Company or Operator Sec. 9 T. 20 R. 3	7 N	Lease J. M. P. M.,	Mommen	t	Fie
Gounty					
County.					
FULL DETAILS OF I FOLLOW INSTRUCTIONS IN THE RU 122 40 8-Thd. New Lapweld casing the Halliburton Method with 250 sack Coment will be drilled out of the ca	was s	ND REGULATIONS set in this we and the hole	OF THE COMP	end ceme	l dry an
FOLLOW INSTRUCTIONS IN THE RU 122 40 4 8-Thd. New Lapweld casing	was s	nd REGULATIONS set in this we and the hole The bailer	of the come	end ceme	dry and
FOLLOW INSTRUCTIONS IN THE RU 122 40 8-Thd. New Lapweld casing the Halliburton Method with 250 sack Cement will be drilled out of the ca allowed to stand undisturbed for one again to determine if any water has	was s	nd REGULATIONS set in this we and the hole The bailer	of the come	end ceme	dry and
FOLLOW INSTRUCTIONS IN THE RU 122 40 8-Thd. New Lapweld casing the Halliburton Method with 250 sack Cement will be drilled out of the ca allowed to stand undisturbed for one again to determine if any water has	was s	nd REGULATIONS set in this we and the hole The bailer	of the come.	end ceme	dry and the lated the
12½ 40 8-Thd. New Lapweld casing the Halliburton Method with 250 sack Cement will be drilled out of the ca allowed to stand undisturbed for one again to determine if any water has drilling will them be resumed.	was s	et in this we and the hole . The bailer mulated. If r	of the come all at 227 will then will then to water he	be bailed n be run t as accumu	dry and the lated the
pproved	was s	nd REGULATIONS set in this we and the hole The bailer	of the come all at 227 will then will then to water he	be bailed in be run as accumulation	dry and the lated the
pproved	was s	and the hole The bailer mulated. If r	of THE COME all at 227 will then will then to water h	be bailed in be run as accumulation	dry and the lated the
pproved	was s sing hour accus	and the hole and the bailer mlated. If r	will then will the to water he	be bailed in be run as accumulation	dry and to botto
pproved	was s sing hour accus	and the hole The bailer mlated. If r	will then will the will the to water he company or comp	be bailed in be run as accumulated a	dry anko botto
12½" 40# 8-Thd. New Lapweld casing the Halliburton Method with 250 sack Cement will be drilled out of the ca allowed to stand undisturbed for one again to determine if any water has drilling will then be resumed.	was s sing hour accus	and the hole and the bailer mlated. If r	will then will the will the to water he company or comp	be bailed in be run as accumulated a	dry and ke bottom lated the

The state of the s

en de la composition La composition de la La composition de la

and the second of the second o