

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Skelly Oil Company
Company or Operator

Robbs, New Mexico
Address

Lucell Van Niten Well No. 1 in CHASE/4 of Sec. 9, T. 20S

R. 37E, N. M. P. M., Lea Field, Monument County.

Well is 660 feet south of the North line and 660 feet east of the line of Lease

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Lucell Van Niten, Address Monument, New Mexico

If Government land the permittee is, Address

The Lessee is Skelly Oil Company, Address Box 1650, Tulsa, Okla.

Drilling commenced November 28 1936 Drilling was completed January 8 1937

Name of drilling contractor Davidson Drilling Company, Address Fort Worth, Texas

Elevation above sea level at top of casing 5552 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"	40	8	LE	240'	CP			
9-5/8"	36	8	RAW	2632'	CP			
7"	24	10	SS	3812'	CP			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13"	13" O.D.	240'	225	Halliburton		
11"	9-5/8"	2632'	400	Halliburton		
8-1/4"	7" O.D.	3812'	200	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 5800 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing January 7 1937
The production of the first 24 hours was 246 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

G. B. Lambert, Driller
S. V. Ferrel, Driller
Driller
Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 9 day of January, 1937

Notary Public, Santa Fe, New Mexico
Name [Signature]
Date January 8, 1937

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	100	100	Sand and Caliche
100	135	35	Caliche
135	233	98	Sand and Shells
233	243	10	Red Bed
243	340	97	Red Bed and Sand
340	373	33	Sand and Shells
373	820	444	Red Bed, Sand, and Shells
820	1023	203	Sand, Shale, and Red Rock
1023	1110	87	Red Rock
1110	1243	133	Red Rock and anhydrite shells
1243	1332	77	Salt and anhydrite shells
1332	1425	93	Red Rock and Sand
1425	1524	99	Anhydrite and Salt
1524	1691	167	Salt and Shale
1691	1810	119	Salt and Potash
1810	1937	127	Salt, Anhydrite, and Potash
1937	2050	113	Salt and anhydrite
2050	2263	213	Anhydrite, Salt, and Potash
2263	2385	117	Anhydrite and Lime
2385	2438	53	Anhydrite, Lime, and Gyp
2438	2483	45	Anhydrite and Lime
2483	2515	32	Anhydrite, Lime and Gyp
2515	2656	151	Anhydrite and Lime
2656	2707	41	Soft Lime and Sand
2707	2815	108	Anhydrite and Lime
2815	2856	41	Anhydrite, Lime, and Sand
2856	3152	296	Anhydrite and Lime
3152	3204	42	Lime
3204	3227	23	Broken Lime and Sand
3227	3289	62	Broken Lime
3289	3332	43	Broken Lime and Sand
3332	3585	253	Lime
3585	3698	113	Grey Lime and Hard Sand
3698	3672	74	Broken Lime
3672	3694	22	Broken Lime and Sand
3694	3716	22	Broken Lime
3716	3776	60	Lime
3776	3815	39	Broken Lime
3815	3840	25	Lime Pay
3840	3890	40	Lime Pay
3890'			