

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Skelly Oil Company

Tulsa, Oklahoma

Company or Operator

Address

Van Etten

Well No. 5

in CNW SE

of Sec. 9

T. 20

Lease

R. 37

N. M. P. M.

Monument

Field,

Lea

County.

Well is 3300 feet south of the North line and 1980 feet west of the East line of Section 9

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Lucile Van Etten Address Hobbs, New Mexico

If Government land the permittee is Address

The Lessee is Address

Drilling commenced May 12, 1937 Drilling was completed June 12, 1937

Name of drilling contractor Davidson Drilling Co. Address Ft. Worth, Texas

Elevation above sea level at top of casing 3552 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 3800' to 3875' No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
13"	40#	8	LW	133'8"				
9-5/8"	36#	8	EW	1175'				
7"	22#	10	EW	3779'4"				
Tubing								
2-1/2"	6.5	10	SS	3898'				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15-1/2"	13"	153	150	Halliburton		
11"	9-5/8"	1168	400	Halliburton		
8-1/4"	7"	3749	600	Halliburton		
Tubing	2-1/2"	3873		Swung		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3875 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing June 16, 1937
The production of the first 24 hours was 4776 barrels of fluid of which 98 % was oil; %
emulsion; 2% Drig water; and % sediment. Gravity, Be 34.0
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

G. D. Lambert, Driller Clyde Ragsdale, Driller
J. C. Ray, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 12

Hobbs, New Mex.

July 13, 1937

day of July, 19

Name

J. E. Cooper

FORMATION RECORD

3017-3200

FROM	TO	THICKNESS IN FEET	FORMATION
0	144	144	Sand & Caliche
144	160	16	Red Bed
160	375	215	Red Bed, Red Rock & Sand
375	625	250	Red Bed
625	747	122	Red Bed & Sand
747	1053	306	Red Bed, Red Rock & Sand
1053	1149	96	Red Bed & Shells
1149	1168	19	Anhydrite
1168	1180	12	Lime
1180	1300	120	Anhydrite
1300	1470	170	Salt & Red Bed
1470	1540	70	Anhydrite & Salt
1540	1582	42	Anhydrite & Potash
1582	1869	287	Anhydrite, Potash & Salt
1869	1905	36	Anhydrite & Potash
1905	1985	80	Salt
1985	2200	215	Salt & Potash
2200	2251	51	Salt, Potash & Anhydrite
2251	2391	140	Salt & Potash Streaks
2391	2413	22	Anhydrite & Lime Shells
2413	2450	37	Salt, Potash & Anhydrite
2450	2514	64	Anhydrite
2514	2596	82	Anhydrite & Lime
2596	2620	24	Anhydrite & Potash
2620	2690	70	Anhydrite & Brown Lime
2690	2710	20	Anhydrite & Blue Shale
2710	2761	51	Broken Anhydrite
2761	2854	93	Anhydrite & Lime
2854	2900	46	Anhydrite
2900	2918	18	Broken Lime
2918	2932	14	Anhydrite & Gypsum
2932	2970	38	Anhydrite & Lime
2970	3008	38	Anhydrite
3008	3073	65	Anhydrite & Brown Lime
3073	3622	549	Lime
3622	3634	12	Gray Lime
3634	3657	23	Lime
3657	3667	10	Gray Lime
3667	3734	67	Lime
3734	3745	11	Gray Lime
3745	3750	5	Lime
3750	3775	25	Lime
3775	3803	28	Gray Lime
3803	3841	38	Lime
3841	3862	21	Broken Lime
3862	3875	13	Brown Lime